



048-2413537F 052-1932447



Produktskizze



h (m)	E0 [®] (lx)	ø (m)
1	5980	0.71
2	1500	1.42
3	660	2.13
4	370	2.84
5	240	3.54



Decke Einbau
schwenkbar max. 35°
Rotierbarkeit 360°
Verkehrsweiß RAL 9016 ¹
Montage Set Verkehrsweiß
IP20
2810 lm

3000 K
CRI \geq 90
L90 / 50000 h
initial MacAdam \leq 3 SDCM
R _g : 100 R _f : 89 R _{f(1-15)} : 89
MR 0.56 MDER 0.51

flood | Ausstrahlwinkel 39°
PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

DALI-2 1 DALI Addr.
SK2 220-240 V
System 27.0 W
System 104 lm/W ³

mit Rand
Durchmesser 112 mm Höhe 106 mm
0.59 kg

Durchmesser 108 mm
min. Deckenstärke 5 mm | max. Deckenstärke 25 mm
Einbautiefe 130 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Volllast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Montage- anleitung



Beleuchtungs- rechner

