

SASSO PRO 100

adjustable

flush trimless

048-2410538W 052-1921447



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Einbau

schwenkbar max. 35°

Rotierbarkeit 360°

Schwarz, RAL9005¹

Montage Set Verkehrsweiß

IP20

1300 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100, R_f: 89, R_{f(1-15)}: 89

MR 0.56

MDER 0.51

Optisch

wide flood

Ausstrahlwinkel 57°

UGR < 19, ≥ 65° < 3000 cd/m²

PstLM ≤ 1.0²

SVM ≤ 0.4²

Elektrisch

DALI-2

14.7 W

SK2 220-240V

88 lm/W

1 DALI Addr.

Abmessungen

randlos

Durchmesser 105 mm

Höhe 106 mm

1.7 kg

Ausschnitt

Durchmesser 116 mm

min. Deckenstärke 12.5 mm

max. Deckenstärke 25 mm

Einbautiefe 110 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Volllast (ungedimmt)


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



Produktskizze

