

SASSO PRO 100

adjustable

offset trimless

048-2410438W 052-1931448



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Einbau

schwenkbar max. 35°

Rotierbarkeit 360°

Schwarz, RAL9005¹

Montage Set Tiefschwarz

IP20

1240 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100, R_f: 89, R_{f(1-15)}: 86

MR 0.49

MDER 0.44

Optisch

wide flood

Ausstrahlwinkel 57°

UGR < 19, ≥ 65° < 3000 cd/m²

PstLM ≤ 1.0²

SVM ≤ 0.4²

Elektrisch

DALI-2

14.7 W

SK2 220-240V

84 lm/W

1 DALI Addr.

Abmessungen

randlos

Länge 105 mm

Breite 113 mm

Höhe 106 mm

0.66 kg

Ausschnitt

Durchmesser 116 mm

min. Deckenstärke 12.5 mm

max. Deckenstärke 25 mm

Einbautiefe 130 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



Produktskizze

