

# MINO 40 mid lumen

suspended

042-121403GH



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke | Abgehängt

Weiß Aluminium | RAL 9006 <sup>1</sup>

IP20

2720 lm

1360 lm/m

## LED

3000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>(f-15)</sub>: 89

MR 0.61 | MDER 0.55

## Optisch

High Performance Opal | opal (lambertsch)

PstLM  $\leq$  1.0 <sup>2</sup> | SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

SK1 | 220-240 V

System 23.4 W

System 116 lm/W <sup>3</sup>

12 W/m

## Abmessungen

Länge 2008 mm | Breite 40 mm | Höhe 65 mm


3.2 kg

<sup>1</sup> RAL Code


<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

