



MINO CIRCLE

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; pendant fitting with cable suspension; with integrated tool-less suspension height adjustment; incl. transparent feed; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; sound absorbing elements available

DE Ringförmiger Leuchtenkörper aus gerolltem Aluminiumstrangpressprofil nahtlos verschweißt; Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung an der Leuchte; inkl. transparenter Einspeiseleitung; Lichteinsatz bestehend aus hochreflektierend lackiertem Aluminiumdruckguss für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; mikroprismatische PMMA-Abdeckung inkl. Diffusorfolie zur Reduktion der Leuchtdichte bei homogener Ausleuchtung; optional mit direk t/indirekter Abstrahlcharakteristik für zusätzliche Akzentuierung der Decke und mehr Sehkomfort; energieeffiziente LEDs mit sehr guter Farbwiedergabe; schallabsorbierende Elemente erhältlich

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
up to 132lm/W
L90 @ 50 000h
DALI-2
opal, microprismatic

Types

suspended



Luminaire colours



Light distributions



DiiA® standards
251, 252, 253



direct/indirect
illumination



microprismatic



acoustic
elements

Order options

SUSPENSION	
cable 1500 mm	2
cable 1500 mm/canopy central	4

COLOUR TEMPERATURE	
3000K	5
4000K	6

CONTROL	
DALI-2	

LUMINAIRE COLOUR	
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
special colours*	X

*canopy always in white

LIGHT OPTIC COVER	
opal high performance	H
microprismatic	Z

Options on request

COLOUR RENDERING INDEX	
CRI ≥ 90	

CONTROL	
Casambi	



MINO 60 CIRCLE 1000 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
65W	3000K	7130lm	0 3 4 - 2 1 2 3 4
	4000K	7550lm	



DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
87W	3000K	↓ 7120 / ↑ 3190 lm	0 3 4 - 2 1 3 3 4
	4000K	↓ 7540 / ↑ 3380 lm	




MINO 60 CIRCLE 1500 suspended




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
99W	3000K	11400lm	0 3 4 - 2 1 0 3 4
	4000K	12100lm	



DIRECT / INDIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
132W	3000K	↓ 11400 / ↑ 5100 lm	0 3 4 - 2 1 1 3 4
	4000K	↓ 12100 / ↑ 5400 lm	




MINO 60 CIRCLE 3000 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
198W	3000K	23000lm	0 3 4 - 2 2 1 4 3 7 H
	4000K	24300lm	

other configurations see MINO 60 CURVE system



MINO 60 CIRCLE 6000 suspended



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
396W	3000K	45900lm	0 3 4 - 2 2 1 6 3 7 H
	4000K	48600lm	

other configurations see MINO 60 CURVE system

Light distributions



opal
direct/indirect



microprismatic
direct/indirect

LUMINOUS FLUX value calculated for CRI ≥ 80, colour white, cover opal

Acoustic elements

see page 608