



MINO CIRCLE

ceiling


EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; sound absorbing elements available; energy-efficient LEDs with very good colour rendering

DE Ringförmiger Leuchtenkörper aus gerolltem Aluminiumstrangpressprofil nahtlos verschweißt; Oberfläche pulverbeschichtet; Lichteinsatz bestehend aus hochreflektierend lackiertem Aluminiumdruckguss für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; mikroprismatische PMMA-Abdeckung inkl. Diffusorfolie zur Reduktion der Leuchtdichte bei homogener Ausleuchtung; schallabsorbierende Elemente erhältlich; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 123lm/W
 L90 @ 50 000h
 DALI-2
 opal, microprismatic

Types




Luminaire colours



Light distribution



DiiA® standards
 251, 252, 253



Order options

COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL

DALI-2

MATERIAL COLOUR

☐ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours	X

LIGHT OPTIC COVER

opal high performance	H
microprismatic	Z


Options on request

COLOUR RENDERING INDEX


CRI ≥ 90

CONTROL

Casambi




MINO 60 CIRCLE 1000 ceiling



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
65W	3000K	7130lm	034-2112::3☐☐
	4000K	7550lm	


MINO 60 CIRCLE 1500 ceiling



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
99W	3000K	11400lm	034-2110::3☐☐
	4000K	12100lm	

MINO 60 CIRCLE 3000 ceiling




DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
198W	3000K	23000lm	034-2114::37H
	4000K	24300lm	

other configurations see MINO 60 CURVE system

MINO 60 CIRCLE 6000 ceiling



DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
396W	3000K	45900lm	034-2116::37H
	4000K	48600lm	

other configurations see MINO 60 CURVE system

Acoustic elements

see page 608