



## Allgemein

Decke , Track

schwenkbar max. 310°

Rotierbarkeit 360°

Weiß , RAL 9016 <sup>1</sup>

IP20

957<sup>2</sup>, 979<sup>3</sup>, 1030<sup>4</sup>, 1050<sup>5</sup>, 1090<sup>6</sup>, 1090<sup>7</sup> lm

## LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>(f-ls)</sub>: 90

MR 0.86

MDER 0.78

## Optisch

wide flood<sup>2</sup>, medium<sup>3</sup>, flood<sup>4</sup>, flood<sup>5</sup>, spot<sup>6</sup>, super spot<sup>7</sup>

Ausstrahlwinkel 64°<sup>2</sup>, 30°<sup>3</sup>, 38°<sup>4</sup>, 40°<sup>5</sup>, 19°<sup>6</sup>, 10°<sup>7</sup>

PstLM ≤ 1.0<sup>5 2 6 3 4 7 8</sup>

SVM ≤ 0.4<sup>5 2 6 3 4 7 8</sup>

## Elektrisch

DIM POTI

220-240 V

System 14.7 W

System 65<sup>2</sup>, 67<sup>3</sup>, 70<sup>4</sup>, 71<sup>5</sup>, 74<sup>6</sup>, 74<sup>7</sup> lm/W<sup>9</sup>

SK1

## Abmessungen

Durchmesser 70 mm

Höhe 98 mm

0.92 kg

werkzeuglose Montage

<sup>1</sup> RAL Code <sup>2</sup> 64 Grad <sup>3</sup> 30 Grad <sup>4</sup> 38 Grad <sup>5</sup> 40 Grad <sup>6</sup> 19 Grad <sup>7</sup> 10 Grad

<sup>8</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>9</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Montage-anleitung



## Beleuchtungs-rechner






Lichtverteilung



Produktskizze



super spot 10°

h (m)	E0° (lx)	ø (m)
1	25600	0.18
2	6400	0.36
3	2800	0.53
4	1600	0.71
5	1000	0.89

spot 19°

h (m)	E0° (lx)	ø (m)
1	6650	0.33
2	1660	0.65
3	740	0.98
4	420	1.31
5	270	1.63

medium 30°

h (m)	E0° (lx)	ø (m)
1	2220	0.54
2	560	1.08
3	250	1.63
4	140	2.17
5	90	2.71

flood 38°

h (m)	E0° (lx)	ø (m)
1	1830	0.69
2	460	1.37
3	200	2.06
4	110	2.75
5	70	3.43

flood 40°

h (m)	E0° (lx)	ø (m)
1	1870	0.72
2	470	1.44
3	210	2.16
4	120	2.88
5	70	3.60

wide flood 64°

h (m)	E0° (lx)	ø (m)
1	790	1.24
2	198	2.48
3	88	3.72
4	49	4.96
5	32	6.19