



DOC

surface


EN Round surface mounted luminaire, housing in die-cast aluminium; central decorative disc made of galvanized sheet steel attached by magnet; surface powder coated; opal cover for completely homogeneous illumination; with increased transmission and diffusion; energy-efficient LEDs with very good colour rendering; degree of protection IP54, with pressure compensation valve; ambient temperatures from -20°C to +50°C; ø180 mm: suitable for through wiring

DE Runde Anbauleuchte, Leuchtenkörper aus Aluminiumdruckguss; zentrale Dekorscheibe aus verzinktem Stahlblech mittels Magnet befestigt; Oberfläche pulverbeschichtet; opale Abdeckung für absolut homogene Ausleuchtung; mit erhöhter Transmission und Diffusion; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schutzart IP54, mit Druckausgleichsventil; Umgebungstemperaturen von -20°C bis +50°C; ø180 mm: geeignet für Weiterverdrahtung

Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM
bis zu 104 lm/W
L90 / 50000 h
nicht dimmbar
IP54, IK09

Types




Farbe



Lichtverteilung





DOC 180 surface

CRI
≥ 80

220-240 V

IP54

IK 09

OPAL non DIM, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.5 W	3000 K	1340 lm	99 lm/W	0 8 8 - 2 7 1 0 5 1



DOC 360 surface

CRI
≥ 80


220-240 V

IP54

IK 09

OPAL non DIM, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
27.8 W	3000 K	2890 lm	104 lm/W	0 8 8 - 2 7 2 0 5 1



Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8
grey aluminium RAL 9007	D