INO 700 circle acoustic

034-370211W



Projekt / Typ Notizen Anzahl / Datum



 $Akustikelement\ aus\ hochwertigem,\ selbsttragendem\ PET-Filz\ mit\ schallabsorbierenden\ Eigenschaften,$ bestehend aus mindestens 50 % post-consumer recyceltem PET; Bauform rund; optisch und haptisch hochwertige Oberfläche, Weiß; Farbabweichungen möglich; zur Montage an den INO circle suspended Seilabhängungen, oberhalb der Leuchte; nachträgliche Anbringung möglich;

Allgemein

Leuchte / Schiene | Montiert

Abmessungen

Durchmesser 648 mm | Höhe 9 mm

0.84 kg

Acoustics

Alpha w (α_w) bis zu 0.6 1

SAC (Schallabsorptionsklasse) bis zu C 1

NRC bis zu 0.55 1

SAA bis zu 0.57 1

Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

¹ Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle, cavity 100cm

Montageanleitung



INO 700 circle acoustic

luminaire mounted 034-370211W




Projekt / Typ		
Notizen		
Anzahl / Datum		

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.2	0.27	0.33	0.4	0.5	0.57

Sound absorption coefficient (ap)



INO circle acoustic

Acoustic data calculations based on INO CIRCLE ACOUSTIC 700 circle: cavity 100cm