

reddot winner 2022



SPIO 60

recessed


EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system or with magnetic attachment; for trimless installation in plasterboard ceilings; paintable cover; shadow joint between cover and mounting set optionally fillable; or with trim; choice of adjustable or fixed symmetric radiation characteristic; high quality lens system; uncluttered ceiling look through recessed lighting level; reduced light-emitting surface (only \varnothing 10 mm); no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler aus Aluminiumdruckguss; werkzeuglose Montage im Montageset durch Kugelschnappsystem oder mittels Magnetbefestigung; für randlosen Einbau in Gipskartondecken; überstreichbare Abdeckplatte; Schattenfuge zwischen Abdeckplatte und Montageset optional verspachtelbar; oder mit umlaufendem Rand; wahlweise einstellbar oder starr symmetrische Abstrahlcharakteristik; hochwertige Linsenoptik; ruhiges Deckenbild durch zurückversetzte Leuchtenebene; reduzierte Lichtaustrittsfläche (nur \varnothing 10 mm); keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K
 CRI \geq 90, 3 SDCM
 up to 60 lm/W
 L95 @ 50000h
 non DIM, DALI-2

Types



Colours



Light distributions




version with black trim




10mm light output area



trimless installation



paintable cover



LFO lens technology

Order options

COLOUR TEMPERATURE	••
2700 K	4
3000 K	5

MATERIAL COLOUR

traffic white RAL9016

paintable cover

BEAM ANGLE

flood 35°	F
wide flood 44°	W

Options on request





COLOUR TEMPERATURE

4000 K

CONCRETE HOUSING

primed concrete ceiling

exposed concrete ceiling



SPIO 60 downlight



DOWNLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
11.9 W 12 Vf 1050 mA	718 lm	0 4 8 - 1 5 1 0 •• 1 7 ▲

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 2 6 9 6 1 1 7

MOUNTING SET WITH TRIM for intermediate ceilings 2–25 mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 1 5 9 7 2 0 7
<input checked="" type="radio"/> jet black RAL 9005	0 4 8 - 1 5 9 7 2 0 8

SPIO 60 adjustable



ADJUSTABLE

INSET POWER	LUMINOUS FLUX	ORDER CODE
11.9 W 12 Vf 1050 mA	685 lm	0 4 8 - 1 5 2 0 •• 1 7 ▲

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 1 5 9 8 1 0 7

MOUNTING SET WITH TRIM for intermediate ceilings 2–25 mm

COLOUR	ORDER CODE
<input type="radio"/> traffic white RAL9016	0 4 8 - 1 5 9 7 1 0 7
<input checked="" type="radio"/> jet black RAL 9005	0 4 8 - 1 5 9 7 1 0 8

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
1050 mA non DIM	η 85 %	111-38-28	0 0 2 - 9 0 7 8 7
1050 mA DALI-2	η 85 %	143-43-30	0 0 2 - 9 0 7 8 8

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W 48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1–2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200–1050 mA settable const. current		
2 × 42 W 48 V DC U _{OUT} 10–40 V		

for more details and components see XAL 22 catalog, page 980

INSET POWER is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens wide flood, 2700 K -5 %