

TASK direct / indirect power

free standing double long

X059-2902058Z



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Bodenmontage | Stehend

Tiefschwarz | RAL 9005 ¹

IP20

indirekt 14700 lm | direkt 4800 lm

gesamt 19500 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_f: 90 | R_[1-15]: 89

MR 0.61 | MDER 0.56

Optisch

Microprismatic | microprismatic

UGR ≤ 13 | $\geq 65^\circ$ < 3000 cd/m²

PstLM $\leq 1.0^2$ ³ | SVM $\leq 0.4^2$ ³

Elektrisch

touch DIM an Stange

SK1 | 220-240 V

System 161 W

System 121 lm/W ⁴

Abmessungen

H-Form


Länge 1750 mm | Breite 320 mm | Höhe 2137 mm

¹ RAL Code ² kombinierte


³ Wert von umgebendem Produkt bei Vollast (ungedimmt)

⁴ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung

