



MINO 60 offset

surface

EN Luminaire housing from extruded aluminium profile, angular design; surface powder coated; luminaire, ball proof version to DIN 18032-3 and DIN 57710 part 13 / VDE 0710 part 13; not suitable for indoor tennis centers (or halls with comparable ball sizes); light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; offset lighting level; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; Oberfläche pulverbeschichtet; Leuchte laut DIN 18032-3 und DIN 57710 Teil 13/VDE 0710 Teil 13 ballwurfsicher ausgeführt; nicht für Tennishallen geeignet (oder Hallen mit vergleichbaren Ballgrößen); Lichteinsatz bestehend aus hochreflektierend lackiertem Strangpressprofil für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; zurückversetzte Leuchtenebene; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000K, 4000K
 CRI ≥ 80, 3 SDCM
 up to 120 lm/W
 L90 @ 50000h
 non DIM, DALI-2
 opal high performance

Types

surface



Colours



Light distribution



direct




DiiA® standards
 251, 252, 253



ball-impact-resistant



tunable white
 2700–6500K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	☐☐
3000K	5
4000K	6

CONTROL	⬆️⬆️
non DIM	1
DALI-2	3

MATERIAL COLOUR	☑️
○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8

LIGHT OPTIC COVER

opal high performance

Options on request

COLOUR RENDERING INDEX

CRI ≥ 90

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

tunable white 2700–6500K

DALI-2 DT8

INDIVIDUAL MATERIAL COLOUR

☑️ MINO 60 ceiling system



MINO 60 offset surface



MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
8.7W	3000K	871lm	575	0 4 6 - 4 7 L 2 ☐☐ 1 ☑️ H
	4000K	923lm		
13W	3000K	1310lm	875	0 4 6 - 4 7 L 3 ☐☐ 1 ☑️ H
	4000K	1380lm		
15.3W	3000K	1740lm	1175	0 4 6 - 4 7 L 4 ☐☐ 1 ☑️ H
	4000K	1850lm		
19.2W	3000K	2180lm	1475	0 4 6 - 4 7 L 5 ☐☐ 1 ☑️ H
	4000K	2310lm		
31W	3000K	3490lm	2347	0 4 6 - 4 7 L 8 ☐☐ 1 ☑️ H
	4000K	3690lm		

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
13.8W	3000K	1440lm	575	0 4 6 - 4 7 M 2 ☐☐☐☐ 1 ☑️ H
	4000K	1530lm		
20.6W	3000K	2160lm	875	0 4 6 - 4 7 M 3 ☐☐☐☐ 1 ☑️ H
	4000K	2290lm		
27.5W	3000K	2880lm	1175	0 4 6 - 4 7 M 4 ☐☐☐☐ 1 ☑️ H
	4000K	3050lm		
34W	3000K	3600lm	1475	0 4 6 - 4 7 M 5 ☐☐☐☐ 1 ☑️ H
	4000K	3810lm		
55W	3000K	5760lm	2347	0 4 6 - 4 7 M 8 ☐☐☐☐ 1 ☑️ H
	4000K	6100lm		