

# BO 45

intrack 2 lamps

180-7240538S



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke | Track

schwenkbar max. 90°

Rotierbarkeit 360°

Tiefschwarz | RAL 9005 <sup>1</sup>

IP20

2220 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100 | R<sub>f</sub>: 91 | R<sub>t(1-15)</sub>: 89

MR 0.59 | MDER 0.53

## Optisch

spot | Ausstrahlwinkel 12°

PstLM ≤ 1.0<sup>2 3 4 5</sup> | SVM ≤ 0.4<sup>2 3 4 5</sup>

## Elektrisch

DALI-2 | 1 DALI Addr.

SK2 | 220-240 V

System 30 W

System 74 lm/W <sup>6</sup>

## Abmessungen

Durchmesser 45 mm | Höhe 120 mm

0.6 kg

<sup>1</sup> RAL Code <sup>2</sup> soft lens BO 45 007-1965980

<sup>3</sup> oval lens BO 45 007-1965880


<sup>4</sup> wallwasher lens BO 45 007-1965780

<sup>5</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>6</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Lichtverteilung



spot 12°

h (m)	E0° (lx)	ø (m)
1	14000	0.21
2	3500	0.42
3	1600	0.63
4	900	0.84
5	600	1.06

## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

