

# BO 55 intrack 1 lamp

180-7330638F



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke | Track

schwenkbar max. 90°

Rotierbarkeit 360°

Tiefschwarz | RAL 9005 <sup>1</sup>

IP20

2190 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 98 | R<sub>f</sub>: 90 | R<sub>t(1-15)</sub>: 88

MR 0.8 | MDER 0.72

## Optisch

flood | Ausstrahlwinkel 37°

PstLM ≤ 1.0<sup>2 3 4 5</sup> | SVM ≤ 0.4<sup>2 3 4 5</sup>

## Elektrisch

DALI-2 | 1 DALI Addr.

SK2 | 220-240 V

System 24.5 W

System 89 lm/W <sup>6</sup>

## Abmessungen

Durchmesser 55 mm | Höhe 140 mm

0.71 kg


<sup>1</sup> RAL Code <sup>2</sup> wallwasher lens BO 55 007-1965790

<sup>3</sup> soft lens BO 55 007-1965990 <sup>4</sup> oval lens BO 55 007-1965890

<sup>5</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>6</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Lichtverteilung



flood 37°

h (m)	EO° (lx)	ø (m)
1	5980	0.67
2	1500	1.34
3	660	2.01
4	370	2.68
5	240	3.35

## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

