

# SETA 60 CONEX

## reflector direct plug / socket

surface / suspended system

058-4024538B



Projekt / Typ

Notizen

Anzahl / Datum



### Allgemein

Decke | Abgehängt

Tiefschwarz | RAL 9005 <sup>1</sup>

Chrom dunkel

IP20

1890 lm

### LED

3000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.56 | MDER 0.51

### Optisch

Reflector | symmetric

UGR  $\leq 16$  |  $\geq 65^\circ$   $< 1500$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$  <sup>2</sup> | SVM  $\leq 0.4$  <sup>2</sup>

### Elektrisch

DALI-2 | 1 DALI Addr.

SK1 | 220-240 V

System 18.6 W

System 102 lm/W <sup>3</sup>

Stecker / Buchse

### Abmessungen

Länge 1181 mm | Breite 60 mm | Höhe 60 mm


2.8 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

### Lichtverteilung



### Produktskizze



### Montageanleitung



### Beleuchtungsrechner

