

# TASK direct / indirect asymmetric power

free standing T-shape

059-29511TXZ



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Bodenmontage | Stehend

Spezialfarben

IP20

indirekt 11000 lm | direkt 2030 lm

gesamt 13030 lm

## LED

4000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 96 | R<sub>f</sub>: 90 | R<sub>t(1-5)</sub>: 87

MR 0.75 | MDER 0.68

## Optisch

Microprismatic | microprismatic

UGR  $\leq 13$  |  $\geq 65^\circ$   $< 3000$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$  <sup>1</sup> | SVM  $\leq 0.4$  <sup>1</sup>

## Elektrisch

Loxone Air / touch DIM on pole

SK1 | 220-240 V

System 95 W

System 137 lm/W <sup>2</sup>

## Abmessungen

T-Form


Länge 800 mm | Breite 320 mm | Höhe 1920 mm

<sup>1</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)


<sup>2</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montageanleitung

