

TASK direct / indirect asymmetric power

free standing T-shape

059-29510T8Z



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Bodenmontage | Stehend

Tiefschwarz | RAL 9005 ¹

IP20

indirekt 10300 lm | direkt 1900 lm

gesamt 12200 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 | R_f: 90 | R_{t(1-5)}: 89

MR 0.61 | MDER 0.56

Optisch

Microprismatic | microprismatic

UGR ≤ 10 | $\geq 65^\circ$ < 3000 cd/m²

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Elektrisch

Loxone Air / touch DIM an Stange

SK1 | 220-240 V

System 97 W

System 126 lm/W ³

Abmessungen

T-Form


Länge 800 mm | Breite 320 mm | Höhe 1920 mm

¹ RAL Code


² Wert von umgebendem Produkt bei Volllast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung

