

# MOVE IN 45 square

trim

063-8421417S 063-8842118 002-90720



Projekt / Typ \_\_\_\_\_

Notizen \_\_\_\_\_

Anzahl / Datum \_\_\_\_\_



## Allgemein

Decke , Halbeinbau \_\_\_\_\_

Weiß , RAL9016 <sup>1</sup> \_\_\_\_\_

Montage Set Tiefschwarz \_\_\_\_\_

IP20 \_\_\_\_\_

1020 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optisch

spot \_\_\_\_\_

Ausstrahlwinkel 12° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Elektrisch

DALI-2 \_\_\_\_\_

14.5 W \_\_\_\_\_

SK2 220-240V \_\_\_\_\_

70 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Abmessungen

mit Rand \_\_\_\_\_

Durchmesser 78 mm \_\_\_\_\_

Höhe 105 mm \_\_\_\_\_

0.24 kg \_\_\_\_\_

## Ausschnitt

Durchmesser 65 mm \_\_\_\_\_


min. Deckenstärke 2 mm \_\_\_\_\_

max. Deckenstärke 25 mm \_\_\_\_\_

Einbautiefe 175 mm \_\_\_\_\_

<sup>1</sup> RAL Code  
<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Lichtverteilung



spot 12°

h (m)	E0° (lx)	ø (m)
1	12900	0.21
2	3200	0.42
3	1400	0.63
4	800	0.84
5	500	1.06

## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

