



Projekt / Typ

Notizen

Anzahl / Datum

**Allgemein**

Decke | Track

Spotlinseneinsatz

Tiefschwarz | RAL 9005 <sup>1</sup>

IP20

5140 lm

2060 lm/m

**LED**

3000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCMR<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>(1-15)</sub>: 89

MR 0.61 | MDER 0.55

**Optisch**

wide flood

UGR  $\leq$  16 |  $\geq 65^\circ$   $< 1500$  cd/m<sup>2</sup>PstLM  $\leq$  1.0 <sup>2</sup> | SVM  $\leq$  0.4 <sup>2</sup>**Elektrisch**

DALI-2 | 1 DALI Addr.

SK2 | 220-240 V

System 41 W


System 125 lm/W <sup>3</sup>

17 W/m

**Abmessungen**

Länge 2500 mm | Breite 43 mm | Höhe 13 mm

1.08 kg

<sup>1</sup> RAL Code<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)<sup>3</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts**Montage-  
anleitung****Beleuchtungs-  
rechner****Lichtverteilung****Produktskizze**