

# MINO 60 high lumen

ceiling / suspended system

007-93M5137 006-16152G 046-400501G



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Abgehängt

Grau , RAL9006 <sup>1</sup>

1900 lm/m

IP20

2800 lm

## LED

4000 K

CRI  $\geq$  90

L90 / 50000 h

photobiologische Sicherheit RG 0 - kein Risiko

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 90

MR 0.81

MDER 0.74

## Optisch

Microprismatic

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

29.1 W

SK1 220-240V

96 lm/W

1 DALI Addr.

20 W/m

## Abmessungen

mit Rand

Länge 1472 mm

Breite 60 mm

Höhe 80 mm

4 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

