

# MINO 60 high lumen

ceiling / suspended system

007-93M5037 006-16152Z 046-400501G



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke | Abgehängt

Grau | RAL 9006 <sup>1</sup>

IP20

2590 lm

1760 lm/m

## LED

3000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>f(15)</sub>: 89

MR 0.61 | MDER 0.55

## Optisch

Microprismatic | microprismatic

PstLM  $\leq$  1.0 <sup>2</sup> | SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2 | 1 DALI Addr.

SK1 | 220-240 V

System 29.1 W

System 89 lm/W <sup>3</sup>

20 W/m

## Abmessungen

mit Rand

Länge 1472 mm | Breite 60 mm | Höhe 80 mm

3.8 kg


<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

