

# MINO 60 high lumen

ceiling / suspended system

007-93M2037 006-16062H 046-400201G



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Abgehängt

Grau , RAL9006 <sup>1</sup>

2080 lm/m

IP20

1190 lm

## LED

3000 K

CRI  $\geq$  90

L90 / 50000 h

photobiologische Sicherheit RG 0 - kein Risiko

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.61

MDER 0.55

## Optisch

High Performance Opal

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

13.2 W

SK1 220-240V

90 lm/W

1 DALI Addr.

23 W/m

## Abmessungen

mit Rand

Länge 572 mm

Breite 60 mm

Höhe 80 mm

1.65 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Produktskizze



## Montage- anleitung



## Beleuchtungs- rechner

