

SASSO 60 round

wall


EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

DE Zylindrische Wandanbauleuchte aus Aluminium; Lichteinsatz lackiert; Oberfläche Gehäuse pulverbeschichtet; wahlweise symmetrisch direkte oder direkt/indirekte Abstrahlcharakteristik; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige Lichtverteilung; präzise Abstrahlcharakteristik durch hochwertige Linsensystem; Montage Variante DIRECT wahlweise zur Boden- oder Deckenaufhellung; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 4000 K
CRI $\geq$ 90 / 2 SDCM
bis zu $\downarrow$ 713 lm / $\uparrow$ 712 lm
bis zu 70 lm/W
L80 / 50000 h
DALI-2, nicht dimmbar
IP20

Types



Farbe



Innenfarbe



Lichtverteilung



direct and
direct / indirect
illumination




high quality
lens



easy mounting



CRI $\geq$ 95 2
SDCM
(optional)




SASSO 60 round direct wall



OPAL LENS | DIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.3 W	2700 K	661 lm	64 lm/W	0 4 8 - 3 1 5 0 4    O
	3000 K	686 lm	67 lm/W	0 4 8 - 3 1 5 0 5    O
	4000 K	716 lm	70 lm/W	0 4 8 - 3 1 5 0 6    O

The data values for the luminous flux may differ for specific order options by -11%.



SASSO 60 round direct / indirect wall



OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.6 W	2700 K	↓659/↑657 lm	64 lm/W	0 4 8 - 3 1 6 0 4    O
	3000 K	↓683/↑682 lm	66 lm/W	0 4 8 - 3 1 6 0 5    O
	4000 K	↓713/↑712 lm	69 lm/W	0 4 8 - 3 1 6 0 6    O

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white	7
				gold dust	9