

048-2612119M 048-2699317 002-90790



Projekt / Typ

## Notizen

Anzahl / Datum



## Decke | Einbau

Gold | RAL 260-M <sup>1</sup>

Montage Set Verkehrsweiß

Vorderseite IP44 | Rückseite IP20

2200 lm

Einsatz 103 lm/W<sup>2</sup>

## 4000 K

CRI  $\geq 90$

180 / 50

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>q</sub>: 98 | R<sub>f</sub>: 90 | R<sub>{f1-15}</sub>: 88

MR 0.8 | MDER 0.72

## medium | Ausstrahlwinkel 27°

UGR  $\leq 16$  |  $\geq 65^\circ$  <3000 cd/m<sup>2</sup>

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

## DALI-2 | 1 DALI Addr.

SK2 | 220-240 V

System 250 W |

total fixtures 21.3 W

36 Vf | 300 mA

50 VI | 500 IIIA

mit Rand

Länge 147 mm | Breite 81 mm | Höhe 48 mm

4.7 kg

Länge 138 mm | Breite 73 mm

min. Deckenstärke 2 mm | max. Deckenstärke 25 mm

Einbautiefe 100 mm

## Produktskizze

