




## Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19
bis zu 116 lm/W
L80 / 50000 h
DALI-2, nicht dimmbar
front IP44, back IP20

### Types




### Farben

### Lichtverteilung

# **SPADO 100 / 150** round

recessed

EN Round or square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

DE Runder oder quadratischer Leuchtenkörper aus Aluminiumdruckguss; mit umlaufendem Rand; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; werkzeuglose Montage mittels Schnappfederverschluss; Reflektor aus Polycarbonat, chrom poliert; symmetrische Abstrahlcharakteristik; Leuchtenebene zurückversetzt; energieeffiziente LEDs mit sehr guter Farbwiedergabe; externer Konverter für Deckeneinwurf, für Weiterverdrahtung geeignet; Betriebsgerät geeignet für den Betrieb an einem Zentralbatterie-System





DiiA® standards
251, 252, 253



glare control
(UGR ≤ 19)



splash water
protection
(IP44)





## **SPADO 100** round downlight trim

CRI ≥ 80 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | IP20 IP44 | X-PERT | X-PERT

**WIDE FLOOD** 49°, traffic white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 9.3 W | 3000 K | 934 lm | 100 lm/W | 049-31115 ◆ 7O |
| | 4000 K | 989 lm | 106 lm/W | 049-31116 ◆ 7O |







## **SPADO 150** round downlight trim

CRI ≥ 80 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | IP20 IP44 | X-PERT | X-PERT

**WIDE FLOOD** 52°, traffic white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 16.4 W | 3000 K | 1810 lm | 110 lm/W | 049-31215 ◆ 7O |
| | 4000 K | 1910 lm | 116 lm/W | 049-31216 ◆ 7O |
| 27.5 W | 3000 K | 2950 lm | 107 lm/W | 049-31235 ◆ 7O |
| | 4000 K | 3130 lm | 114 lm/W | 049-31236 ◆ 7O |




## Mounting accessories

**EXPOSED CONCRETE MOUNTING HOUSING**

| L·W·H (mm) | ORDER CODE |
|---|---|
| 295·295·160 | 049-31912 10 |

for SPADO 150 round

**PRIMED CONCRETE MOUNTING HOUSING**

| L·W (mm) | ORDER CODE |
|---|---|
| 310·170 | 049-31914 10 |

**Order options**

| CONTROL | ◆ |
|---|---|
| non DIM | 1 |
| DALI-2 | 3 |

| COLOUR | |
|---|---|
| traffic white | RAL 9016 |