

## Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19, UGR ≤ 22
bis zu 118 lm/W
L80 / 50000 h
DALI-2, nicht dimmbar
front IP44, back IP20

### Types




### Farben

### Lichtverteilung

# **SPADO 150** square

recessed

EN Square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

DE Quadratischer Leuchtenkörper aus Aluminiumdruckguss; mit umlaufendem Rand; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; werkzeuglose Montage mittels Schnappfederverschluss; Reflektor aus Polycarbonat, chrom poliert; symmetrische Abstrahlcharakteristik; Leuchtenebene zurückversetzt; energieeffiziente LEDs mit sehr guter Farbwiedergabe; externer Konverter für Deckeneinwurf, für Weiterverdrahtung geeignet; Betriebsgerät geeignet für den Betrieb an einem Zentralbatterie-System




DiiA® standards
251, 252, 253



glare control
(UGR ≤ 19)



splash water
protection
(IP44)



## **SPADO 150** square downlight trim

CRI ≥ 80 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | IP20 IP44 | X-PERT | X-PERT







**WIDE FLOOD** 56°, traffic white, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 16.4 W | 3000 K | 1830 lm | 112 lm/W | 049-315157O |
| | 4000 K | 1940 lm | 118 lm/W | 049-315167O |
| 27.5 W | 3000 K | 2990 lm | 109 lm/W | 049-315257O |
| | 4000 K | 3170 lm | 115 lm/W | 049-315267O |

## Mounting accessories

**EXPOSED CONCRETE MOUNTING HOUSING**

| L·W·H (mm) | ORDER CODE |
|---|---|
| 400·260·160 | 049-319221O |

**PRIMED CONCRETE MOUNTING HOUSING**

| L·W (mm) | ORDER CODE |
|---|---|
| 310·170 | 049-319141O |

## Order options

| CONTROL | | COLOUR | |
|---|---|---|---|
| non DIM | 1 | traffic white | RAL 9016 |
| DALI-2 | 3 | | |