


Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19
bis zu ↓ 5.290 lm / ↑ 5.230 lm
bis zu 159 lm/W
L85 / 50000 h
Abdeckung: Microprismatic
DALI-2, eigenständiger ESSENTIAL Sensor
IP20

Types



Farben

Lichtverteilung

SONIC


suspended

EN Conical light housing in die-cast aluminium; surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; incl. feeder cable or with height adjustable rod suspension (chrome), feed in rod; direct / indirect light distribution; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; Acoustic elements made of high quality, self-supporting, at least 75% recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties available

DE Konischer Leuchtenkörper aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung an der Leuchte; inkl. Einspeiseleitung oder mit kürzbarer Pendelrohrabhängung (chrom), Einspeiseleitung in Pendelrohr; direkt / indirekte Abstrahlcharakteristik; Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom und maximale Deckenaufhellung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; Akustikelemente aus hochwertigem, selbsttragenden, mind. 75% recycelten PET-Filz (hohe akustische Performance durch Materialaufdopplung) oder als akustisch wirksamer Leuchtenschirm (große Farbauswahl) mit schallabsorbierenden Eigenschaften erhältlich



DiiA® standards
251, 252, 253



microprismatic
UGR ≤ 19



sensor version
available




acoustic
absorber




direct / indirect
illumination










SONIC suspended

CRI ≥ 80 | UGR ≤ 19 | 220-240 V | 1 ADDR. | X-PERT | X-PERT | presence | brightness

DIRECT / INDIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
66.0 W	3000 K	↧5000/↥4940 lm	151 lm/W	0 5 9 - 7 ♁ 2 1 5 ◆ ◪ P
	4000 K	↧5290/↥5230 lm	159 lm/W	0 5 9 - 7 ♁ 2 1 6 ◆ ◪ P

Planning Information





SONIC suspended, 69 W, 4000 K
direct / indirect with absorber

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 | 0.5 | 0.2
Maintenance factor	0.8
Mounting height	2.25 m

CALCULATION SURFACE


Surface dimensions	Floor
Surface height	0.5 m

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

Acoustic accessories



ABSORBER RING 1050


COLOUR	Ø·H (mm)	ORDER CODE
anthracite	1050·50	0 5 9 - 7 7 1 1 2 1 B
marble grey	1050·50	0 5 9 - 7 7 1 1 2 1 D
black	1050·50	0 5 9 - 7 7 1 1 2 1 L
limestone	1050·50	0 5 9 - 7 7 1 1 2 1 S
white	1050·50	0 5 9 - 7 7 1 1 2 1 W
felt grey	1050·50	0 5 9 - 7 7 1 1 2 1 G

only in combination with SONIC suspended or SONIC free standing

Order options

MOUNTING ♁	CONTROL ◆	COLOUR ◪	COLOUR
cable 1500 mm (min. 500 mm) 2	DALI-2 3	black grey RAL 7021 6	marble grey RAL 7047
rod 1000 mm 4	stand alone ESSENTIAL sensor 7	pure white RAL 9010 7	felt grey RAL 7037
		special colours X	limestone RAL 070 70 20
			anthracite RAL 7021


ABSORBER RING 1280



COLOUR	Ø·H (mm)	ORDER CODE
anthracite	1280·50	0 5 9 - 7 7 1 1 1 1 B
marble grey	1280·50	0 5 9 - 7 7 1 1 1 1 D
black	1280·50	0 5 9 - 7 7 1 1 1 1 L
limestone	1280·50	0 5 9 - 7 7 1 1 1 1 S
white	1280·50	0 5 9 - 7 7 1 1 1 1 W
felt grey	1280·50	0 5 9 - 7 7 1 1 1 1 G

only in combination with SONIC suspended or SONIC free standing

SOUNDCAP



COLOUR	Ø·H (mm)	ORDER CODE
marble grey	527·300	0 5 9 - 7 7 3 1 1 1 D
felt grey	527·300	0 5 9 - 7 7 3 1 1 1 G
black	527·300	0 5 9 - 7 7 3 1 1 1 L
white	527·300	0 5 9 - 7 7 3 1 1 1 W
acoustic special colours	527·300	0 5 9 - 7 7 3 1 1 1 X
limestone	527·300	0 5 9 - 7 7 3 1 1 1 S
anthracite	527·300	0 5 9 - 7 7 3 1 1 1 B

only in combination with SONIC suspended or SONIC free standing; bracket colour white; other bracket colours on request

Order options

COLOUR	
marble grey	RAL 7047
felt grey	RAL 7037
limestone	RAL 070 70 20
anthracite	RAL 7021

C&P Immobilien AG

Österreich

Architekt
INNOCAD Architecture,
Graz

Lighting Design
INNOCAD Architecture,
Graz

Fotograf
Paul Ott



Verwendete Produkte



SONIC suspended




MINO 60 ceiling / suspended system




SASSO 100 round adjustable recessed 1 lamp



SASSO 100 round downlight recessed 1 lamp



SASSO 100 round wallwasher recessed 1 lamp




SASSO 100 round wallwasher/floor recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









MERCEDES BENZ Lounge

Schweiz

Architekt
Kauffmann Theilig & Partner

Lighting Design
TLD Planungsgruppe GmbH

Fotograf
Andreas Keller Fotografie



Verwendete Produkte



SONIC suspended

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com


Inspiration
Création
Impulsion