



TASK

free standing


EN Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

DE Stehleuchte mit rechteckigem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15mm); Standrohr rechteckig; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkt/indirekte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach oben und unten gelenkt; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom; optional: Indirektlichtanteil mit eigenen, schräg gerichteten Platinen für asymmetrische Abstrahlcharakteristik; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker

Quickinfo

3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 UGR \leq 10, UGR \leq 13, UGR \leq 19
 bis zu ↓ 4,370 lm / ↑ 9,320 lm
 bis zu 136 lm/W
 L90 / 50000 h
 Loxone Air / ESSENTIAL Sensor,
 Loxone Air / touch DIM an Stange,
 eigenständiger ESSENTIAL
 Sensor, touch DIM an Stange
 Microprismatic
 IP20

Types



Farbe



Lichtverteilung




suitable for
double
workstation




SENSE sensor
on request



lighting control
by touch DIM on
pole



tunable white
2700 – 6500 K



CRI \geq 98
XPECTRUM
(optional)




TASK free standing u-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↓4100/↑3350 lm	111 lm/W	0 5 9 - 2 9 4 3 0 <input checked="" type="checkbox"/> Z
	4000 K	↓4370/↑3560 lm	118 lm/W	0 5 9 - 2 9 4 3 1 <input checked="" type="checkbox"/> Z



MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↓2400/↑7330 lm	128 lm/W	0 5 9 - 2 9 4 2 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2550/↑7800 lm	136 lm/W	0 5 9 - 2 9 4 2 1 <input checked="" type="checkbox"/> Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↓1900/↑8630 lm	112 lm/W	0 5 9 - 2 9 4 1 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2030/↑9320 lm	121 lm/W	0 5 9 - 2 9 4 1 1 <input checked="" type="checkbox"/> Z




TASK free standing t-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↓4100/↑3350 lm	111 lm/W	0 5 9 - 2 9 5 3 0 <input checked="" type="checkbox"/> Z
	4000 K	↓4370/↑3560 lm	118 lm/W	0 5 9 - 2 9 5 3 1 <input checked="" type="checkbox"/> Z



MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↓2400/↑7330 lm	128 lm/W	0 5 9 - 2 9 5 2 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2550/↑7800 lm	136 lm/W	0 5 9 - 2 9 5 2 1 <input checked="" type="checkbox"/> Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↓1900/↑8630 lm	112 lm/W	0 5 9 - 2 9 5 1 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2030/↑9320 lm	121 lm/W	0 5 9 - 2 9 5 1 1 <input checked="" type="checkbox"/> Z

Order options

CONTROL		COLOUR	
Loxone Air / ESSENTIAL sensor	S	white aluminium RAL 9006	6
Loxone Air / touch DIM on pole	T	pure white RAL 9010	7
touch DIM on pole	5	jet black RAL 9005	8
stand alone ESSENTIAL sensor	7	special colours	X

OFFICE OMV

Österreich

Fotograf
Kurt Kuball



Verwendete Produkte



TASK free standing

