



## TASK

wall


**EN** Rectangular housing made of aluminium with rounded edges; ultra low-profile design (only 15 mm); surface powder coated; suitable for wall mounting; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect component with special PCBs with asymmetrical light distribution; for optimum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering

**DE** Rechteckiger Leuchtenkörper aus Aluminium mit abgerundeten Kanten; extrem flache Bauform (nur 15 mm); Oberfläche pulverbeschichtet; geeignet für Wandmontage; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; Lichtlenkung mittels hochreflektierenden Reflektormaterials; Indirektlichtanteil mit eigenen Platinen mit asymmetrischer Lichtverteilung; für optimale Deckenaufhellung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90 / 3 SDCM (initial MacAdam)  
 bis zu ↓ 1,970 lm / ↑ 3,760 lm  
 bis zu 127 lm/W  
 L90 / 50000 h  
 DALI-2  
 Microprismatic  
 IP20

### Types



### Farbe



### Lichtverteilung



asymmetrical  
ceiling  
illumination




### TASK wall




MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
45.0 W	3000 K	↓1850/↑3530 lm	120 lm/W	0 5 9 - 2 0 3 2 0 3 <input checked="" type="checkbox"/> Z
	4000 K	↓1970/↑3760 lm	127 lm/W	0 5 9 - 2 0 3 2 1 3 <input checked="" type="checkbox"/> Z



### Planning Information



#### TASK wall

46W, 4000K, direct/indirect power

#### ROOM VALUES

Room dimensions	5.4 × 4.0 × 2.8m
Reflection factor	0.7   0.5   0.2
Maintenance factor	0.8
Mounting height	2.25m

#### CALCULATION SURFACE

Surface dimensions	Floor
Surface height	0m

#### GLARE EVALUATION

Table Classification	X=4H   Y=8H   S=0.25H
UGR transversal	≤ 19
UGR axial	≤ 19



### Order options

COLOUR		<input checked="" type="checkbox"/>
pure white RAL 9010	7	
jet black RAL 9005	8	