




Quickinfo

3000 K, 4000 K
 CRI ≥ 95 / 2 SDCM (initial MacAdam)
 bis zu 17 lm/W
 L85 / 50000h
 DALI-2, DIM POTI
 IP20

Types



Farbe



PABLO shutter / iris / gobo

EN Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter in spotlight housing; COB (Chip on Board) technology - maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; contour spotlight for precise rectangular or round shape; easy adjustment by 4 shading elements or by iris-shaped shade made of stainless steel; incl. high quality bi-convex glass lens; sharp object focusing through adjustable lens; focus using rubber adjustment ring on spotlight head; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, available as an accessory

DE Stromschienenstrahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; 360° dreh- und 310° schwenkbar; Konverter im Strahlergehäuse; COB (Chip on Board) Technologie - höchste Effizienz; keine Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Konturstrahler für exakte rechteckige oder runde Formgebung; einfache Einstellung durch 4 Abschattenelemente oder durch irisförmige Abschatter aus Edelstahl; inkl. hochwertiger bikonvexer Glaslinse; scharfe Objekt-Fokussierung durch justierbare Linse; Fokussierung mittels gummiertem Verstellring am Strahlerkopf; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen; Adapter-Fixierung wahlweise werkzeuglos mittels Rändel- oder Feststellschraube (Schraubendreher erforderlich); Punktauslass, wahlweise in Anbaugehäuse bzw. Einbaugehäuse, als Zubehör erhältlich



compatible with
 MOVE IT PRO
 45



DiiA® standards
 251, 252, 253



360° rotatable,
 310° tiltable



shutter / iris /
 gobo



DIM POTI /
 rotation lock




PABLO shutter track



31°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.0 W	3000 K	201 lm	14 lm/W	1 8 0 - 5 3 8 0 0 4
	4000 K	220 lm	16 lm/W	1 8 0 - 5 3 8 0 1 4
23.0 W	3000 K	298 lm	13 lm/W	1 8 0 - 5 3 8 1 0 4
	4000 K	327 lm	14 lm/W	1 8 0 - 5 3 8 1 1 4




PABLO iris track




32°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.0 W	3000 K	210 lm	15 lm/W	1 8 0 - 5 4 8 0 0 4
	4000 K	231 lm	17 lm/W	1 8 0 - 5 4 8 0 1 4
23.0 W	3000 K	312 lm	14 lm/W	1 8 0 - 5 4 8 1 0 4
	4000 K	343 lm	15 lm/W	1 8 0 - 5 4 8 1 1 4




Planning Information

PABLO shutter




possible shapes of illumination

PABLO iris



possible shapes of illumination

Illumination size



A (mm)	H (mm)	Ø (mm)
1000	396	560
2000	792	1120
3000	1188	1680

Mounting accessories (optional)

RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm

Ø-H (mm)	ORDER CODE
151-60	1 8 6 - 0 7 2 2 7 4

Order options

MOUNTING	8	CONTROL	4	COLOUR	4
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8


SURFACE HOUSING / POINT OUTLET

Ø-H (mm)
120-32

ORDER CODE

1 8 6 - 0 7 2 2 8

Order options

MOUNTING	<input checked="" type="checkbox"/>	CONTROL	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8