



# SONO IP54

surface


**EN** Round luminaire housing in die-cast aluminium; surface powder coated; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

**DE** Runder Leuchtenkörper aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; geeignet für Wand- oder Deckenmontage; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

## Quickinfo

3000 K, 4000 K  
 CRI ≥ 80 / 3 SDCM (initial MacAd  
 bis zu 143 lm/W  
 L90 / 50000 h  
 DALI-2, nicht dimmbar  
 Opal  
 IP54, IK07

## Types



## Farbe



## Lichtverteilung




DiiA® standards  
 251, 252, 253




easy mounting  
 by click-  
 mechanism



dust & insect  
 protection (IP  
 54)



tunable white  
 2700 – 6500 K  
 (optional)




### SONO 260 IP54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.6 W	3000 K	950 lm	125 lm/W	8 7 1 - 9 1 2 6 5 ◆ 7 0
	4000 K	1010 lm	133 lm/W	8 7 1 - 9 1 2 6 6 ◆ 7 0




### SONO 350 IP54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	2090 lm	131 lm/W	8 7 1 - 9 1 3 6 5 ◆ 7 0
	4000 K	2210 lm	139 lm/W	8 7 1 - 9 1 3 6 6 ◆ 7 0




### SONO 450 IP54 surface



OPAL | DIRECT pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	3060 lm	132 lm/W	8 7 1 - 9 1 4 6 5 ◆ 7 0
	4000 K	3240 lm	140 lm/W	8 7 1 - 9 1 4 6 6 ◆ 7 0



#### Order options


CONTROL		COLOUR	
non DIM	1	pure white	RAL 9010
DALI-2	3		



**SONO 600 IP54 surface**



**OPAL | DIRECT** pure white, CRI ≥ 80



SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
43.0 W	3000 K	5830 lm	136 lm/W	8 7 1 - 9 1 5 6 5 <b>7 0</b>
	4000 K	6170 lm	143 lm/W	8 7 1 - 9 1 5 6 6 <b>7 0</b>

**Mounting accessories (optional)**

**DISMOUNTING TOOL**

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0