

SONO LOOP IP54

surface


EN Round luminaire housing in die-cast aluminium; surface powder coated; fitted bezel in rolled, seamless welded aluminium profile; suitable for wall or ceiling mounting; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

DE Runder Leuchtenkörper aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; aufgesetzter Ring aus gerolltem und nahtlos verschweißtem Aluminiumprofil; geeignet für Wand- oder Deckenmontage; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 bis zu 136 lm/W
 L90 / 50000 h
 DALI-2, nicht dimmbar
 Opal
 IP54, IK07

Types



Farbe



Lichtverteilung




DiiA® standards
 251, 252, 253




easy mounting
 by click-
 mechanism



dust & insect
 protection (IP
 54)



tunable white
 2700 – 6500 K
 (optional)




SONO LOOP 260 ip54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
7.0 W	3000 K	881 lm	126 lm/W	8 7 1 - 8 1 2 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	933 lm	133 lm/W	8 7 1 - 8 1 2 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O




SONO LOOP 350 ip54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	8 7 1 - 8 1 3 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	2050 lm	129 lm/W	8 7 1 - 8 1 3 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O




SONO LOOP 450 ip54 surface




OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	8 7 1 - 8 1 4 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	3010 lm	130 lm/W	8 7 1 - 8 1 4 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O



Order options

CONTROL		COLOUR	
non DIM	1	grey aluminium RAL 9007	D
DALI-2	3	pure white RAL 9010	7



SONO LOOP 600 ip54 surface



OPAL | DIRECT CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5410 lm	129 lm/W	8 7 1 - 8 1 5 6 5 <input checked="" type="checkbox"/> <input type="checkbox"/> O
	4000 K	5730 lm	136 lm/W	8 7 1 - 8 1 5 6 6 <input checked="" type="checkbox"/> <input type="checkbox"/> O

Order options

CONTROL		COLOUR	
non DIM	1	grey aluminium RAL 9007	<input checked="" type="checkbox"/> D
DALI-2	3	pure white RAL 9010	<input type="checkbox"/> 7