



LENO

trimless system


EN Low profile recessed channel; suitable for trimless installation in 12.5mm plasterboard ceilings; suitable for wall or ceiling mounting; designed for continuous lighting systems; surface powder coated; special edge design with grooves for better adhesion of filler; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; optional with asymmetric light distribution; energy-efficient LEDs with very good colour rendering; incl. external converter for ceiling insertion

DE Extrem flacher Einbaukanal; geeignet für den randlosen Einbau in 12,5mm Gipskartondecken; geeignet für die Wand- oder Deckenmontage; ausgelegt für durchgehende Lichtsysteme; Oberfläche pulverbeschichtet; spezielle Randausbildung mit Rillen für bessere Haftung der Spachtelmasse; einfache Montage ohne Schneiden der Unterkonstruktion; absturzsicherer Lichteinsatz aus stranggepresstem Aluminiumprofil werkzeuglos mittels Magnethalter in Kanal einsetzbar; seitlich eingekoppeltes Licht durch LGP-Body (Light-Guiding-Prism) und hocheffizientem Reflektor nach unten gelenkt; homogen ausgeleuchtete, satinierte (bündig oder herausragend) oder mikroprismatische Abdeckung aus PMMA; optional mit asymmetrischer Lichtverteilung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; inkl. externem Konverter für Deckeneinwurf

Quickinfo

3000 K, 4000 K
 CRI \geq 80 / 3 SDCM (initial MacAdam)
 UGR \leq 19
 bis zu 140 lm/W
 L90 / 50000 h
 DALI-2
 Asymmetric Wallwasher, High Performance Opal, Jut-Out, Microprismatic
 IP40 / back IP20 / SK2 / 220-240 V

Types




Farbe



Lichtverteilung



DiiA® standards
 251, 252, 253




microprismatic
 UGR \leq 19



quick
 installation

LENO TRIMLESS SYSTEM



INSTALLATION CHANNEL trimless

L·W·H (mm)

613-92-13

1221-92-13

1830-92-13

2438-92-13

ORDER CODE



0 5 1 - 8 9 0 0 0 6 7

0 5 1 - 8 9 0 0 1 2 7

0 5 1 - 8 9 0 0 1 8 7

0 5 1 - 8 9 0 0 2 4 7

order installation channel, light inset + mounting accessories separately




LIGHT INSET



MICROPRISMATIC traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1230 lm	124 lm/W	0 5 1 - 8 0 1 2 :: 3 7 G
19.1 W	1221 mm	2450 lm	128 lm/W	0 5 1 - 8 0 1 4 :: 3 7 G
28.6 W	1830 mm	3680 lm	129 lm/W	0 5 1 - 8 0 1 6 :: 3 7 G
37.0 W	2438 mm	4910 lm	133 lm/W	0 5 1 - 8 0 1 8 :: 3 7 G



OPAL traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1300 lm	131 lm/W	0 5 1 - 8 0 1 2 :: 3 7 H
19.1 W	1221 mm	2590 lm	136 lm/W	0 5 1 - 8 0 1 4 :: 3 7 H
28.6 W	1830 mm	3890 lm	136 lm/W	0 5 1 - 8 0 1 6 :: 3 7 H
37.0 W	2438 mm	5190 lm	140 lm/W	0 5 1 - 8 0 1 8 :: 3 7 H

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.

OPAL JUT-OUT traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
9.9 W	613 mm	1240 lm	125 lm/W	0 5 1 - 8 0 1 2 :: 3 7 J
19.1 W	1221 mm	2490 lm	130 lm/W	0 5 1 - 8 0 1 4 :: 3 7 J
28.6 W	1830 mm	3730 lm	130 lm/W	0 5 1 - 8 0 1 6 :: 3 7 J
37.0 W	2438 mm	4970 lm	134 lm/W	0 5 1 - 8 0 1 8 :: 3 7 J



ASYMMETRIC traffic white, CRI ≥ 80, DALI-2

SYSTEM	LENGTH	LUM. FLUX	EFFICACY	ORDER CODE
15.6 W	613 mm	1660 lm	106 lm/W	0 5 1 - 8 0 1 2 :: 3 7 A
30.0 W	1221 mm	3320 lm	111 lm/W	0 5 1 - 8 0 1 4 :: 3 7 A
46.0 W	1830 mm	4990 lm	108 lm/W	0 5 1 - 8 0 1 6 :: 3 7 A
60.0 W	2438 mm	6650 lm	111 lm/W	0 5 1 - 8 0 1 8 :: 3 7 A

Order options

COLOUR TEMPERATURE	COLOUR	RAL 9016
3000 K	5 traffic white	
4000 K	6	

Planning Information



LENO trimless, microprismatic,
19:1W, 4000K

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19

Mounting accessories (optional)



END CAPS trimless 1 pair

W-H (mm)	
92:13	

ORDER CODE

0 5 1 - 8 9 9 0 2 1 7



LINEAR CONNECTOR recessed

TYPE	L-W (mm)	ORDER CODE
1 pair	48-19	0 5 1 - 8 9 9 0 1 1 0
10 pairs	48-19	0 5 1 - 8 9 9 0 1 1 0 · 1 0

Mounting tools accessories (optional)

DISMOUNTING TOOL

TYPE	
vacuum cup	

ORDER CODE

0 8 6 - 3 0 0 0 0

Order options

COLOUR TEMPERATURE	COLOUR	RAL 9016
3000 K	5 traffic white	
4000 K	6	

Vaucluse House, Australia

Australien

Lighting Design
EST Lighting

Fotograf
Katherine Lu



Verwendete Produkte



**LENO trimless
system**





