




**Quickinfo**

6500 K  
 bis zu 217 lm/W  
 DALI-2 ESSENTIAL sensor,  
 DALI-2 SENSE sensor  
 front IP20, IP40, back IP20

**Types**



**Farbe**



**Montage Set**



**SASSO 60 round sensor / emergency**

**EN** Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement


**DE** Runder Einsatz (Notlicht bzw. Sensor); werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand); Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; LED Notlicht-Einsatz: 3 Varianten mit verschiedenen Testmöglichkeiten - Basic mit Prüftaste, Selbsttest mit Status-LED oder Pro DALI mit Überwachung über DALI; Sensor mit DALI-2 Steuerung: 2 Varianten - Basic mit Helligkeits- und Anwesenheitssensor oder Pro mit zusätzlicher Temperatur-, Luftfeuchtigkeits-, Luftqualitäts- und Lärmpegelmessung



quick mounting  
 in soft acoustic  
 ceilings



### SASSO 60 round sensor essential



DALI-2 ESSENTIAL sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 1 1

0 4 8 - 2 6 9 3 1 1 7



60



ø 63



### SASSO 60 round sensor sense



DALI-2 SENSE sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 2 1

0 4 8 - 2 6 9 3 1 2 7



65



ø 63



### SASSO 60 round emergency light





**3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 1 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses



110



**3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 2 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses

**3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 3 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses

#### Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017


## Mounting accessories (required)

		<b>MOUNTING SET trimless</b> for plasterboard ceilings		
COLOUR	PLASTERBOARD CEILING THICKNESS	Ø-H (mm)	ORDER CODE	
traffic white	12.5/15/25 mm	73-29	0 4 8 - 2 6 9 6 1 1 7	
for SASSO 60 round   SPIO 60 downlight				


 60°/115°\*\*  
 non DIM  
 120  
 DALI-2  
 145  
 loop through function  
 \* SASSO 60  
 \*\* SPIO 60

		<b>MOUNTING SET trimless</b> for soft acoustic ceilings		
TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7

 74  
 120  
 non DIM  
 120  
 DALI-2  
 145  
 loop through function


		<b>MOUNTING SET with trim</b> for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-27	0 4 8 - 2 6 9 6 3 9 7	
jet black		80-27	0 4 8 - 2 6 9 6 3 9 8	


 74  
 100  
 non DIM  
 100  
 DALI-2  
 125  
 loop through function

		<b>MOUNTING SET with trim 1 lamp</b> for intermediate ceilings, 2-25 mm		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-40	0 4 8 - 2 6 9 6 3 1 7	
jet black		80-40	0 4 8 - 2 6 9 6 3 1 8	


 73  
 60  
 non DIM  
 100  
 DALI-2  
 125  
 loop through function

## Mounting accessories (optional)

		<b>EXPOSED CONCRETE MOUNTING HOUSING</b>		
COLOUR		L-W-H (mm)	ORDER CODE	
white aluminium		230-230-162	0 4 8 - 2 6 9 5 2 1 0	

		<b>PRIMED CONCRETE MOUNTING HOUSING</b>		
L-W-H (mm)			ORDER CODE	
614-307-120			0 4 8 - 2 6 9 5 1 1 0	
order mounting set separately				

## Mounting tools accessories (optional)

		<b>MOUNTING TOOL</b> for soft acoustic ceilings		
COLOUR		L-W-H (mm)	ORDER CODE	
traffic black		77-77-35	0 4 8 - 2 6 9 5 9 1 8	

## Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017



### Electrical accessories (optional)

#### REPLACEMENT ACCUPACK

**TYPE**

3h battery life

**ORDER CODE**

0 4 8 - 2 6 9 3 9 1 0

---

**Order options**

**COLOUR**

jet black RAL 9005

traffic white RAL 9016



**COLOUR**

white aluminium

traffic black

RAL 9006

RAL 9017