




## Quickinfo

6500 K
bis zu 217 lm/W
DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20, IP40, back IP20

### Types




### Farben

### Montage Set

# **SASSO 60** round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement

DE Runder Einsatz (Notlicht bzw. Sensor); werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand); Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; LED Notlicht-Einsatz: 3 Varianten mit verschiedenen Testmöglichkeiten - Basic mit Prüftaste, Selbsttest mit Status-LED oder Pro DALI mit Überwachung über DALI; Sensor mit DALI-2 Steuerung: 2 Varianten - Basic mit Helligkeits- und Anwesenheitssensor oder Pro mit zusätzlicher Temperatur-, Luftfeuchtigkeits-, Luftqualitäts- und Lärmpegelmessung



quick mounting
in
soft acoustic
ceilings



60




## **SASSO 60** round sensor essential


360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | presence | brightness

DALI-2 ESSENTIAL sensor

| COLOUR | ORDER CODE |
|---|---|
| jet black | 048 - 269311 1 |
| traffic white | 048 - 269311 7 |



65




## **SASSO 60** round sensor sense


360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | brightness | presence | temp. | sound pr. | $CO_2$ | humidity

DALI-2 SENSE sensor

| COLOUR | ORDER CODE |
|---|---|
| jet black | 048 - 269312 1 |
| traffic white | 048 - 269312 7 |



110




## **SASSO 60** round emergency light

360° | CRI ≥ 80 | 220-240 V

**3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 1.0 W | 6500 K | 217 lm | 217 lm/W | 048 - 269321 |

incl. 3 interchangeable lenses

**3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80

| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 1.0 W | 6500 K | 217 lm | 217 lm/W | 048 - 269322 |

incl. 3 interchangeable lenses

**3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS** 21°-149°x150°, CRI ≥ 80


| SYSTEM | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 1.0 W | 6500 K | 217 lm | 217 lm/W | 048 - 269323 |

incl. 3 interchangeable lenses

**Order options**

| COLOUR | | COLOUR | |
|---|---|---|---|
| jet black RAL 9005 | 1 | white aluminium | RAL 9006 |
| traffic white RAL 9016 | 7 | traffic black | RAL 9017 |


## Mounting accessories (required)




**MOUNTING SET trimless** for plasterboard ceilings


| COLOUR | PLASTERBOARD CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|
| traffic white | 12.5/15/20/25 mm | 73·29 | 048-2696117 |

for SASSO 60 round | SPIO 60 downlight





**MOUNTING SET trimless** for soft acoustic ceilings

| TYPE | COLOUR | CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|---|
| For Rockfon Mono® Acoustic | traffic white | 25-40 mm | 80·25 | 048-2696197 |




**MOUNTING SET with trim** for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 80·27 | 048-2696397 |
| jet black | 80·27 | 048-2696398 |




**MOUNTING SET with trim 1 lamp** for intermediate ceilings, 2-25 mm


| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 80·40 | 048-2696317 |
| jet black | 80·40 | 048-2696318 |

## Mounting accessories (optional)




**EXPOSED CONCRETE MOUNTING HOUSING**

| COLOUR | L·W·H (mm) | ORDER CODE |
|---|---|---|
| white aluminium | 230·230·162 | 048-2695210 |




**PRIMED CONCRETE MOUNTING HOUSING**

| L·W·H (mm) | ORDER CODE |
|---|---|
| 614·307·120 | 048-2695110 |

order mounting set separately

## Mounting tools accessories (optional)




**MOUNTING TOOL** for soft acoustic ceilings

| COLOUR | L·W·H (mm) | ORDER CODE |
|---|---|---|
| traffic black | 77·77·35 | 048-2695918 |

**Order options**

| COLOUR | |
|---|---|
| white aluminium | RAL 9006 |
| traffic black | RAL 9017 |

## Electrical accessories (optional)

### REPLACEMENT ACCUPACK

| TYPE | ORDER CODE |
| --- | --- |
| 3h battery life | 048-269390 |