



Quickinfo

6500 K
bis zu 217 lm/W
DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20, IP40, back IP20

Types



Farben

Montage Set

SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement

DE Runder Einsatz (Notlicht bzw. Sensor); werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand); Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; LED Notlicht-Einsatz: 3 Varianten mit verschiedenen Testmöglichkeiten - Basic mit Prüftaste, Selbsttest mit Status-LED oder Pro DALI mit Überwachung über DALI; Sensor mit DALI-2 Steuerung: 2 Varianten - Basic mit Helligkeits- und Anwesenheitssensor oder Pro mit zusätzlicher Temperatur-, Luftfeuchtigkeits-, Luftqualitäts- und Lärmpegelmessung



quick mounting
in
soft acoustic
ceilings



60



SASSO 60 round sensor essential

360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | presence | brightness

DALI-2 ESSENTIAL sensor

COLOUR	ORDER CODE
jet black	048-269311 1
traffic white	048-269311 7



65



SASSO 60 round sensor sense

360° | 220-240 V | DALI 1 ADDR. | IP20 IP40 | brightness | presence | temp. | sound pr. | CO_2 | humidity

DALI-2 SENSE sensor

COLOUR	ORDER CODE
jet black	048-269312 1
traffic white	048-269312 7



110



SASSO 60 round emergency light

360° | CRI ≥ 80 | 220-240 V

3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048-269321

incl. 3 interchangeable lenses

3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048-269322

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	048-269323

incl. 3 interchangeable lenses

Order options

COLOUR		COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/20/25 mm	73·29	048-269611 7

for SASSO 60 round | SPIO 60 downlight



MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	80·25	048-269619 7



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·27	048-269639 7
jet black	80·27	048-269639 8



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	80·40	048-269631 7
jet black	80·40	048-269631 8

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	048-269521 0



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-269511 0

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings

COLOUR	L·W·H (mm)	ORDER CODE
traffic black	77·77·35	048-269591 8

Order options

COLOUR	
white aluminium	RAL 9006
traffic black	RAL 9017

Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE	ORDER CODE
3h battery life	048-269390