

INO square

suspended


EN Square aluminium luminaire housing; surface powder coated; pendant fitting with cable suspension; height adjustment without tools; incl. transparent feed; electronic operating unit installed in the canopy; completely homogeneously illuminated, satinised PMMA cover; inwards facing emission characteristics; direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring

DE Quadratischer Leuchtenkörper aus Aluminium; Oberfläche pulverbeschichtet; abgedandelt mit Seilabhängung; werkzeuglose Höhenverstellung; inkl. transparenter Einspeiseleitung; elektronisches Betriebsgerät im Baldachin verbaut; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; nach innen gerichtete Abstrahlcharakteristik; direkt/indirekte Abstrahlcharakteristik für zusätzliche Akzentuierung der Decke und mehr Sehkomfort; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90 / 3 SDCM (initial MacAdam)
 bis zu ↓ 4,770 lm / ↑ 4,760 lm
 bis zu 129 lm/W
 L90 / 50000 h
 DALI-2
 High Performance Opal
 IP20

Types



Farbe



Lichtverteilung




Dii[®] standards
 251, 252, 253



direct / indirect
 illumination



tunable white
 2700 – 6500 K
 (optional)



CRI ≥ 98
 XPECTRUM
 (optional)





INO 750 square suspended



OPAL CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
38.0 W	2700 K	↓2170/↑2160 lm	114 lm/W	0 3 4 - 4 4 4 2 4 3 <input checked="" type="checkbox"/> H
	3000 K	↓2280/↑2270 lm	120 lm/W	0 3 4 - 4 4 4 2 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓2390/↑2380 lm	126 lm/W	0 3 4 - 4 4 4 2 6 3 <input checked="" type="checkbox"/> H




INO 1000 square suspended



OPAL CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
51.0 W	2700 K	↓2890/↑2890 lm	113 lm/W	0 3 4 - 4 4 4 3 4 3 <input checked="" type="checkbox"/> H
	3000 K	↓3040/↑3030 lm	119 lm/W	0 3 4 - 4 4 4 3 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓3180/↑3170 lm	125 lm/W	0 3 4 - 4 4 4 3 6 3 <input checked="" type="checkbox"/> H




INO 1250 square suspended



OPAL CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
63.0 W	2700 K	↓3610/↑3610 lm	115 lm/W	0 3 4 - 4 4 4 4 4 3 <input checked="" type="checkbox"/> H
	3000 K	↓3790/↑3790 lm	120 lm/W	0 3 4 - 4 4 4 4 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓3970/↑3970 lm	126 lm/W	0 3 4 - 4 4 4 4 6 3 <input checked="" type="checkbox"/> H



Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> G
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8




INO 1500 square suspended



OPAL CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
74.0 W	2700 K	↓4330/↑4330 lm	117 lm/W	0 3 4 - 4 4 4 5 4 3 <input checked="" type="checkbox"/> H
	3000 K	↓4550/↑4550 lm	123 lm/W	0 3 4 - 4 4 4 5 5 3 <input checked="" type="checkbox"/> H
	4000 K	↓4770/↑4760 lm	129 lm/W	0 3 4 - 4 4 4 5 6 3 <input checked="" type="checkbox"/> H



Order options

COLOUR	
white aluminium RAL 9006	<input checked="" type="checkbox"/> G
special colours	X
pure white RAL 9010	7
jet black RAL 9005	8

Granitlab Coworking

Österreich

Architekt

GHT-Plan GmbH

Lighting Design


GHT-Plan GmbH, AREA
C.I. Design GmbH

Fotograf

Kurt Kuball



Verwendete Produkte



UNICO Q1 / Q4 basic ceiling



BETO suspended



INO square suspended

