

Quickinfo

3000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
bis zu 104 lm/W
L80 / 50000 h
nicht dimmbar
IP54, IK07, IK09

Types



Farben



Lichtverteilung



DOC

surface

EN Round surface mounted luminaire, housing in die-cast aluminium; central decorative disc made of galvanized sheet steel attached by magnet; surface powder coated; opal cover for completely homogeneous illumination; with increased transmission and diffusion; energy-efficient LEDs with very good colour rendering; degree of protection IP54, with pressure compensation valve; ambient temperatures from -20°C to + 50°C; ø180 mm: suitable for through wiring

DE Runde Anbauleuchte, Leuchtenkörper aus Aluminiumdruckguss; zentrale Dekorscheibe aus verzinktem Stahlblech mittels Magnet befestigt; Oberfläche pulverbeschichtet; opale Abdeckung für absolut homogene Ausleuchtung; mit erhöhter Transmission und Diffusion; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schutzart IP54, mit Druckausgleichsventil; Umgebungstemperaturen von -20°C bis +50°C; ø180 mm: geeignet für Weiterverdrahtung



DOC 180 surface

CRI ≥ 80 | 220-240 V | IP54 | IK07 | X-PERT | X-PERT

OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.5 W	3000 K	1340 lm	99 lm/W	088 - 271051





DOC 360 surface

CRI ≥ 80 | 220-240 V | IP54 | IK 09 | X-PERT | X-PERT

OPAL CRI ≥ 80, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.8 W	3000 K	2890 lm	104 lm/W	088 - 272051



Order options

COLOUR	
pure white RAL 9010	7
jet black RAL 9005	8
grey aluminium RAL 9007	D