

Quickinfo

2700 K, 3000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
bis zu 106 lm/W
L80 / 50000 h, L85 / 50000 h, L90 / 100000 h
DALI-2, nicht dimmbar
front IP20

Types



Farben



Montage Set



Lichtverteilung



MOVE IN round

recessed

EN Round spotlight element in aluminium, available in 3 sizes; surface polished chrome, brushed aluminium or powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

DE Rundes Strahlerelement aus Aluminium in 3 Größen; Oberfläche chrom poliert, Aluminium gebürstet oder pulverbeschichtet; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; spezielles Montagewerkzeug zur einfachen Installation des randlosen Gehäuses als Zubehör erhältlich; Strahlerelement werkzeuglos höhenverstellbar: deckenbündig, 25 mm oder 35 mm herausragend; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschattenbildung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör



wallwasher floor optic



trimless installation in plasterboard



tool-free height adjustment







MOVE IN 22 round

CRI ≥ 90 · 2 SDCM · UGR ≤ 10 · III · DALI 1 ADDR. · X-PERT · X-PERT

SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	328 lm	59 lm/W	063-810141 S
	3000 K	346 lm	62 lm/W	063-810151 S

incl. connection cable 600 mm

MEDIUM 26°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	345 lm	62 lm/W	063-810141 M
	3000 K	364 lm	65 lm/W	063-810151 M

incl. connection cable 600 mm

FLOOD 43°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.6 W, 36 Vf, 150 mA	2700 K	371 lm	67 lm/W	063-810141 F
	3000 K	391 lm	70 lm/W	063-810151 F

incl. connection cable 600 mm

WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
5.7 W, 12 Vf, 500 mA	2700 K	357 lm	63 lm/W	063-810141 Y
	3000 K	399 lm	70 lm/W	063-810151 Y

incl. connection cable 600 mm; do not use optical filters







MOVE IN 32 round

CRI ≥ 90 · 2 SDCM · UGR ≤ 10 · cd/m² ≤ 1500 · III · DALI 1 ADDR. · X-PERT

SPOT 18°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	788 lm	91 lm/W	063-811141 S
	3000 K	817 lm	94 lm/W	063-811151 S

incl. connection cable 600 mm

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	821 lm	94 lm/W	063-811141 M
	3000 K	852 lm	98 lm/W	063-811151 M

incl. connection cable 600 mm

FLOOD 34°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W, 36 Vf, 250 mA	2700 K	783 lm	90 lm/W	063-811141 F
	3000 K	813 lm	93 lm/W	063-811151 F

incl. connection cable 600 mm

Order options

COLOUR	
chrome	4
brushed aluminium	6
traffic white RAL 9016	7
jet black RAL 9005	8







MOVE IN 45 round

CRI ≥ 90 · 2 SDCM · UGR ≤ 10 · III · DALI 1 ADDR. · X-PERT · X-PERT

SUPER SPOT 8°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.9 W, 11 Vf, 600 mA	2700 K	406 lm	59 lm/W	063-812141 V
	3000 K	432 lm	63 lm/W	063-812151 V

incl. connection cable 600 mm; do not use optical filters

SPOT 12°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.7 W, 37 Vf, 350 mA	2700 K	1100 lm	87 lm/W	063-812141 S
	3000 K	1150 lm	91 lm/W	063-812151 S

incl. connection cable 600 mm

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1330 lm	100 lm/W	063-812141 M
	3000 K	1380 lm	104 lm/W	063-812151 M

incl. connection cable 600 mm

FLOOD 36°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1360 lm	102 lm/W	063-812141 F
	3000 K	1420 lm	106 lm/W	063-812151 F

incl. connection cable 600 mm

WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.9 W, 36 Vf, 400 mA	2700 K	1340 lm	90 lm/W	063-812141 Y
	3000 K	1340 lm	90 lm/W	063-812151 Y

incl. connection cable 600 mm; do not use optical filters

Mounting accessories (required)



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	56·64	063-881011 7

for MOVE IN 22 round



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	63·93	063-881111 7

for MOVE IN 32 round

Order options

COLOUR	
chrome	4
brushed aluminium	6
traffic white RAL 9016	7
jet black RAL 9005	8



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	75·106	063-881211 7

for MOVE IN 45 round



MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	59·65	063-882011 7
jet black	59·65	063-882011 8

for MOVE IN 22 round



MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	65·93	063-882111 7
jet black	65·93	063-882111 8

for MOVE IN 32 round



MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	77·107	063-882211 7
jet black	77·107	063-882211 8

for MOVE IN 45 round

Mounting tools accessories (optional)



SPECIAL MOUNTING TOOL

TYPE	Ø·H (mm)	ORDER CODE
for MOVE IN 22 | SPIO 20		048-169000 0
for MOVE IN 32 round	83·107	063-891111 0

necessary to install mounting housing trimless



SPECIAL MOUNTING TOOL for ARY | MOVE IN 45 | NOBA trimless | TULA

Ø·H (mm)	ORDER CODE
100·107	063-891211 0

necessary to install mounting housing trimless

Electrical accessories (required)

POWER SUPPLY

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
350 mA | 15 W | DALI-2 | PC2	198-264 V AC	η 87 %	166·29·21	002-907 20
350 mA | 22 W | non DIM | PC2	198-264 V AC	η 89 %	180·30·21	002-907 22
600 mA | 30 W | non DIM | PC1	198-264 V AC	η 89 %	180·30·21	002-907 26

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
600 mA | 40 W | DALI-2 | PC2	198-264 V AC	η 89 %	197·29·21	002-90729
500 mA | 23 W | non DIM | PC2	198-264 V AC	η 88 %	138·30·21	002-90734
500 mA | 15 W | DALI-2 | PC2	198-264 V AC	η 87 %	165·29·21	002-90735
250 mA | 10 W | non DIM | PC2	198-264 V AC	η 80 %	65·39·20	002-90742
250 mA | 10 W | DALI-2 | PC2	198-264 V AC	η 82 %	166·29·21	002-90743
400 mA | DALI-2				002-90791
150 mA | 15 W | DALI-2 | PC2	198-264 V AC	η 87 %	112·29·21	002-90811

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-6520210

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-6121030

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

Optical accessories (optional)



HONEYCOMB LOUVER for BO 32 | JUST 32 | MOVE IN 32 | TARO 32 | TILA 32

COLOUR	Ø·H (mm)	ORDER CODE
jet black	30·3	007-1965168



HONEYCOMB LOUVER for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

COLOUR	Ø·H (mm)	ORDER CODE
jet black	42·3	007-1965188



OVAL LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007-1965860



OVAL LENS for BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007-1965880



SOFT LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007 - 1965960



SOFT LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007 - 1965980



WALLWASHER LENS for BO 32 | MOVE IN 32 | TARO 32 | TILA 32

Ø·H (mm)	ORDER CODE
30·7	007 - 1965760



WALLWASHER LENS for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

Ø·H (mm)	ORDER CODE
42·7	007 - 1965780