


Quickinfo

2700 K, 3000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
bis zu 106 lm/W
L85 / 50000 h, L90 / 100000 h
DALI-2, nicht dimmbar
front IP20

Types



Farben

Montage Set

Lichtverteilung

MOVE IN 45 square

recessed

EN Square spotlight element in aluminium; surface polished chrome, brushed aluminium or powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

DE Quadratisches Strahlerelement aus Aluminium; Oberfläche chrom poliert, Aluminium gebürstet oder pulverbeschichtet; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; spezielles Montagewerkzeug zur einfachen Installation des randlosen Gehäuses als Zubehör erhältlich; Strahlerelement werkzeuglos höhenverstellbar: deckenbündig, 25 mm oder 35 mm herausragend; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschattenbildung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör



trimless installation in plasterboard



tool-free height adjustment



MOVE IN 45 square

CRI ≥ 90 | 2 SDCM | UGR ≤ 10 | III | DALI 1 ADDR. | X-PERT





SUPER SPOT 8°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.9 W, 11 Vf, 600 mA	2700 K	406 lm	59 lm/W	0 6 3 - 8 4 2 1 4 1 ◪ V
	3000 K	432 lm	63 lm/W	0 6 3 - 8 4 2 1 5 1 ◪ V

incl. connection cable 600 mm

SPOT 12°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
12.7 W, 37 Vf, 350 mA	2700 K	1100 lm	87 lm/W	0 6 3 - 8 4 2 1 4 1 ◪ S
	3000 K	1150 lm	91 lm/W	0 6 3 - 8 4 2 1 5 1 ◪ S

incl. connection cable 600 mm

MEDIUM 24°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1330 lm	100 lm/W	0 6 3 - 8 4 2 1 4 1 ◪ M
	3000 K	1380 lm	104 lm/W	0 6 3 - 8 4 2 1 5 1 ◪ M


incl. connection cable 600 mm

FLOOD 36°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W, 36 Vf, 400 mA	2700 K	1360 lm	102 lm/W	0 6 3 - 8 4 2 1 4 1 ◪ F
	3000 K	1420 lm	106 lm/W	0 6 3 - 8 4 2 1 5 1 ◪ F

incl. connection cable 600 mm


Mounting accessories (required)



MOUNTING HOUSING trimless for plasterboard ceilings

COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	9-25 mm	80·54	0 6 3 - 8 8 3 2 1 1 7

for MOVE IN 45 square




MOUNTING HOUSING with trim for ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
traffic white	78·78·55	0 6 3 - 8 8 4 2 1 1 7
jet black	78·78·55	0 6 3 - 8 8 4 2 1 1 8

for MOVE IN 45 square

Mounting tools accessories (optional)



SPECIAL MOUNTING TOOL for ARY | MOVE IN 45 | NOBA trimless | TULA

Ø·H (mm)	ORDER CODE
100·107	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless

Order options


COLOUR	◪
chrome	4
brushed aluminium	6
traffic white RAL 9016	7
jet black RAL 9005	8

Electrical accessories (required)

POWER SUPPLY 198-264 V AC

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
350 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-907220
350 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-907222
400 mA | 22 W | non DIM | PC2	η 89 %	180·30·21	002-907224
600 mA | 30 W | non DIM | PC1	η 89 %	180·30·21	002-907226
400 mA | 15 W | DALI-2 | PC2	η 87 %	166·29·21	002-907228
600 mA | 40 W | DALI-2 | PC2	η 89 %	197·29·21	002-907229

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V SELV

Optical accessories (optional)



HONEYCOMB LOUVER for ARY | BO 45 | JUST 45 | MOVE IN 45 | TARO 45 | TULA micro

COLOUR	Ø·H (mm)	ORDER CODE
jet black	42·3	007-196518 8

Hotel Stoiser

Österreich

Architekt
EDERARCH ZT GmbH

Lighting Design
Eugen Schöberl

Fotograf
Miriam Raneburger



Verwendete Produkte



MOVE IN 45 square recessed

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com





