

MITA square 200 / 360

recessed


EN Square luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

DE Quadratischer Leuchtenkörper aus Aluminiumdruckguss; extrem schlanke Bauform; Einbauleuchte mit umlaufendem Rand; optional: Blindabdeckung zum Einlegen im Innenausschnitt als Zubehör erhältlich; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; hochglänzender Reflektor mit Facettenoptik; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI $\geq$ 80, CRI $\geq$ 90 / 3 SDCM
(initial MacAdam)
UGR $\leq$ 19
bis zu 163 lm/W
L90 / 100000 h, L90 / 75000 h
DALI-2
Reflector
IP20

Types



Farben



Reflektor



Lichtverteilung



suitable for
plasterboard or
grid ceilings



DIN EN 12464-1
UGR $\leq$ 19



tunable white
2700 - 6500 K

MITA SQUARE 200 trim



REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
13.8 W	3000 K	80	chrome	2080 lm	151 lm/W	0 7 4 - 8 3 1 4 5 3 ☒ R
			dark chr.	1490 lm	108 lm/W	0 7 4 - 8 3 1 4 5 3 ☒ B
		90	chrome	1810 lm	131 lm/W	0 7 4 - 8 3 1 4 0 3 ☒ R
			dark chr.	1300 lm	94 lm/W	0 7 4 - 8 3 1 4 0 3 ☒ B
	4000 K	80	chrome	2220 lm	161 lm/W	0 7 4 - 8 3 1 4 6 3 ☒ R
			dark chr.	1590 lm	115 lm/W	0 7 4 - 8 3 1 4 6 3 ☒ B
		90	chrome	1810 lm	131 lm/W	0 7 4 - 8 3 1 4 1 3 ☒ R
			dark chr.	1300 lm	94 lm/W	0 7 4 - 8 3 1 4 1 3 ☒ B
14.2 W	tunable w.	90	chrome	1670 lm	118 lm/W	0 7 4 - 8 3 1 4 D 3 ☒ R
			dark chr.	1200 lm	85 lm/W	0 7 4 - 8 3 1 4 D 3 ☒ B

197×197 60

142

□ 209

□ 92

MITA SQUARE 360 trim



REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
28.5 W	tunable w.	90	chrome	3340 lm	117 lm/W	0 7 4 - 8 3 1 6 D 3 ☒ R
			dark chr.	2390 lm	84 lm/W	0 7 4 - 8 3 1 6 D 3 ☒ B
29.4 W	3000 K	80	chrome	4500 lm	153 lm/W	0 7 4 - 8 3 1 6 5 3 ☒ R
			dark chr.	3220 lm	110 lm/W	0 7 4 - 8 3 1 6 5 3 ☒ B
		90	chrome	3920 lm	133 lm/W	0 7 4 - 8 3 1 6 0 3 ☒ R
			dark chr.	2800 lm	95 lm/W	0 7 4 - 8 3 1 6 0 3 ☒ B
	4000 K	80	chrome	4790 lm	163 lm/W	0 7 4 - 8 3 1 6 6 3 ☒ R
			dark chr.	3430 lm	117 lm/W	0 7 4 - 8 3 1 6 6 3 ☒ B
		90	chrome	3920 lm	133 lm/W	0 7 4 - 8 3 1 6 1 3 ☒ R
			dark chr.	2800 lm	95 lm/W	0 7 4 - 8 3 1 6 1 3 ☒ B
40.0 W	3000 K	80	chrome	5850 lm	146 lm/W	0 7 4 - 8 3 2 6 5 3 ☒ R
			dark chr.	4190 lm	105 lm/W	0 7 4 - 8 3 2 6 5 3 ☒ B
		90	chrome	5100 lm	128 lm/W	0 7 4 - 8 3 2 6 0 3 ☒ R
			dark chr.	3650 lm	91 lm/W	0 7 4 - 8 3 2 6 0 3 ☒ B
	4000 K	80	chrome	6230 lm	156 lm/W	0 7 4 - 8 3 2 6 6 3 ☒ R
			dark chr.	4460 lm	112 lm/W	0 7 4 - 8 3 2 6 6 3 ☒ B
		90	chrome	5100 lm	128 lm/W	0 7 4 - 8 3 2 6 1 3 ☒ R
			dark chr.	3650 lm	91 lm/W	0 7 4 - 8 3 2 6 1 3 ☒ B

348×348 60

43

□ 360

□ 241

Optical accessories (optional)

BLIND COVER square 200

ORDER CODE

0 7 4 - 8 9 1 3 4 1 ☒

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

BLIND COVER square 360

ORDER CODE

0 7 4 - 8 9 1 3 6 1 ☒

Order options

COLOUR		☒
traffic white	RAL 9016	7
jet black	RAL 9005	8