



# UNICO Q1 sensor

recessed

**EN** UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

**DE** UNICO Q1 sensor; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; klirrfrei

## Quickinfo

DALI-2 ESSENTIAL sensor,  
DALI-2 SENSE sensor  
front IP20

### Types

trim



□ 63

trimless



□ 47

### Farbe



### Montage Set



### Lichtverteilung




DiiA® standards  
251, 252, 253



one luminaire  
multiple scenes




plug / socket  
connector




black & gold  
reflector  
(optional)



tunable white  
2700 - 5000 K  
(optional)



### UNICO Q1 sensor essential



jet black, DALI-2 ESSENTIAL sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 0 0



### UNICO Q1 sensor sense




jet black, DALI-2 SENSE sensor

ORDER CODE

0 9 0 - 7 Q 1 0 0 1 0

### Mounting accessories (required)



**MOUNTING SET trimless** for plasterboard ceilings 12.5/15/20/25 mm

L-W-H (mm)

47-47-47

ORDER CODE

0 9 0 - 7 Q 1 0 1 0 0

for UNICO Q1



**MOUNTING SET with trim** for intermediate ceilings, 2-25 mm

COLOUR

jet black

L-W-H (mm)

63-63-30

ORDER CODE

0 9 0 - 7 Q 1 0 2 0 B

traffic white

63-63-30

0 9 0 - 7 Q 1 0 2 0 W

for UNICO Q1

### Order options

#### COLOUR

jet black

RAL 9005

traffic white

RAL 9016