

Quickinfo

DALI-2 ESSENTIAL sensor,
DALI-2 SENSE sensor
front IP20

Types

trim
□ 63

trimless
□ 47

Farben

Montage Set

Lichtverteilung

UNICO Q1 sensor


recessed

EN UNICO Q1 sensor; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; clank-free

DE UNICO Q1 sensor; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; klirrfrei



plug / socket
connector



UNICO Q1 sensor essential

220-240 V · DALI 1 ADDR. · presence · brightness

jet black, DALI-2 ESSENTIAL sensor

ORDER CODE
090-7Q10000






UNICO Q1 sensor sense

220-240 V · DALI 1 ADDR. · brightness · presence · temp. · sound pr. · CO_2 · humidity

jet black, DALI-2 SENSE sensor

ORDER CODE
090-7Q10010

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L·W·H (mm)	ORDER CODE
12.5/15/20/25 mm	47·47·47	090-7Q10100

for UNICO Q1



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L·W·H (mm)	ORDER CODE
jet black	63·63·30	090-7Q1020B
traffic white	63·63·30	090-7Q1020W

for UNICO Q1

Order options

COLOUR	
jet black	RAL 9005
traffic white	RAL 9016