


Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
bis zu ↓ 10.300 lm / ↑ 5.800 lm
bis zu 137 lm/W
L90 / 100000 h
Abdeckung: Opal
DALI-2
IP20

Types



Farben

Lichtverteilung

MINO 60 S CIRCLE

suspended

EN Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; flat design luminaire housing; surface powder coated; pendant fitting with cable suspension, alternatively with canopy central; height adjustment without tools; incl. feed (black or white); converter included in canopy; opal cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering

DE Ringförmiger Leuchtenkörper aus gerolltem Aluminiumstrangpressprofil nahtlos verschweißt; flache Bauform; Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung, wahlweise mit Zentralbaldachin; werkzeuglose Höhenverstellung; inkl. Einspeiseleitung (schwarz oder weiß); Konverter im Baldachin enthalten; opale Abdeckung für homogene Ausleuchtung; mikroprismatische PMMA-Abdeckung inkl. Diffusorfolie zur Reduktion der Leuchtdichte bei homogener Ausleuchtung; optional mit direkt/indirekter Abstrahlcharakteristik für zusätzliche Akzentuierung der Decke und mehr Sehkomfort; energieeffiziente LEDs mit sehr guter Farbwiedergabe




DiiA® standards 251, 252, 253




direct / indirect illumination







*direct/indirect version



*direct/indirect version

MINO 60 S circle 1000 suspended

CRI ≥ 80 | 220-240 V | 1-2 ADDR. | X-PERT | X-PERT

OPAL | DIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
59.0 W	3000 K	6860 lm	116 lm/W	0 3 4 - 7 ♂ 1 2 5 3 ◪ H
	4000 K	7300 lm	124 lm/W	0 3 4 - 7 ♂ 1 2 6 3 ◪ H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
79.0 W	3000 K	↧6860/↥3120 lm	126 lm/W	0 3 4 - 7 ♂ 1 3 5 3 ◪ H
	4000 K	↧7300/↥3550 lm	137 lm/W	0 3 4 - 7 ♂ 1 3 6 3 ◪ H







*direct/indirect version



*direct/indirect version

MINO 60 S circle 1500 suspended

CRI ≥ 80 | UGR ≤22 | 220-240 V | 1-5 ADDR. | X-PERT | X-PERT

OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
83.0 W	3000 K	9630 lm	116 lm/W	0 3 4 - 7 ♂ 1 0 5 3 ◪ H
	4000 K	10300 lm	124 lm/W	0 3 4 - 7 ♂ 1 0 6 3 ◪ H

OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
119.0 W	3000 K	↧9630/↥5100 lm	124 lm/W	0 3 4 - 7 ♂ 1 1 5 3 ◪ H
	4000 K	↧10300/↥5800 lm	135 lm/W	0 3 4 - 7 ♂ 1 1 6 3 ◪ H

Order options

MOUNTING	♂
cable 1500 mm	2
cable 1500 mm / canopy central	4

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G
special colours	X

Dentsu Aegis Network, Zurich

Schweiz

Architekt
Büronauten AG

Lighting Design
Caduff Socker

Fotograf
Z. Gataric Fotografie



Verwendete Produkte



MINO 60 CIRCLE suspended



TULA suspended



TULA MOVE IT 25 / 25 S / 45



MINO 60 S CIRCLE suspended

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com







