


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
bis zu 2.510 lm/m
bis zu 113 lm/W
L85 / 50000 h
DALI-2, nicht dimmbar
Opal
IP44

Types



Farben

Enddeckel

Lichtverteilung

STRETTA

wall

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; opal cover for uniform illumination; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; Leuchtenprofil vorab montierbar; Enddeckel in Leuchtenfarbe pulverbeschichtet oder Aluminium gebürstet; geeignet für Wandmontage; mit dreiseitiger Lichtabstrahlung; opale Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe



wall illumination



splash water protection (IP 44)



CRI ≥ 98 XPECTRUM





STRETTA wall

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-01325 ◆ ◪ H
		4000 K	1480 lm	113 lm/W	057-01326 ◆ ◪ H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-01335 ◆ ◪ H
		4000 K	2220 lm	113 lm/W	057-01336 ◆ ◪ H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-01345 ◆ ◪ H
		4000 K	2950 lm	112 lm/W	057-01346 ◆ ◪ H






STRETTA wall | end caps aluminium

CRI ≥ 90 | 220-240 V | DALI 1 ADDR. | IP 44 | X-PERT

OPAL pure white, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	057-01325 ◆ 2 H
		4000 K	1480 lm	113 lm/W	057-01326 ◆ 2 H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	057-01335 ◆ 2 H
		4000 K	2220 lm	113 lm/W	057-01336 ◆ 2 H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	057-01345 ◆ 2 H
		4000 K	2950 lm	112 lm/W	057-01346 ◆ 2 H



Order options

CONTROL ◆		COLOUR ◪	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8