



## SASSO 60 round

wall

**EN** Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

**DE** Zylindrische Wandanbauleuchte aus Aluminium; Lichteinsatz lackiert; Oberfläche Gehäuse pulverbeschichtet; wahlweise symmetrisch direkte oder direkt/indirekte Abstrahlcharakteristik; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige Lichtverteilung; präzise Abstrahlcharakteristik durch hochwertige Linsensystem; Montage Variante DIRECT wahlweise zur Boden- oder Deckenaufhellung; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
 bis zu ↓ 713 lm / ↑ 712 lm  
 bis zu 70 lm/W  
 L80 / 50000 h  
 DALI-2, nicht dimmbar  
 IP20

### Types



### Farbe



### Innenfarbe



### Lichtverteilung



direct and  
 direct / indirect  
 illumination



high quality lens



easy mounting



CRI  $\geq$  95 2  
 SDCM  
 (optional)




### SASSO 60 round direct wall



#### OPAL LENS | DIRECT 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.3 W	2700 K	661 lm	64 lm/W	0 4 8 - 3 1 5 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	686 lm	67 lm/W	0 4 8 - 3 1 5 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	716 lm	70 lm/W	0 4 8 - 3 1 5 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.



### SASSO 60 round direct / indirect wall



#### OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	2700 K	↓659/↑657 lm	64 lm/W	0 4 8 - 3 1 6 0 4 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	↓683/↑682 lm	66 lm/W	0 4 8 - 3 1 6 0 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	↓713/↑712 lm	69 lm/W	0 4 8 - 3 1 6 0 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



#### Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9