



SASSO 100 round

wall


EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

DE Zylindrische Wandanbauleuchte aus Aluminium; Lichteinsatz lackiert; Oberfläche Gehäuse pulverbeschichtet; wahlweise symmetrisch direkte oder direkt/indirekte Abstrahlcharakteristik; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige Lichtverteilung; präzise Abstrahlcharakteristik durch hochwertige Linsensystem; Montage Variante DIRECT wahlweise zur Boden- oder Deckenaufhellung; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI \geq 90 / 2 SDCM (initial MacAdam)
 bis zu ↓ 1,200 lm / ↑ 1,200 lm
 bis zu 69 lm/W
 L80 / 50000 h
 DALI-2, nicht dimmbar
 IP20

Types



Farbe



Innenfarbe



Lichtverteilung



direct and
direct / indirect
illumination



high quality lens



easy mounting



CRI \geq 95 2
SDCM
(optional)




SASSO 100 round direct wall



OPAL LENS | DIRECT 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	0 4 8 - 3 4 5 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	1150 lm	64 lm/W	0 4 8 - 3 4 5 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3500 K	1170 lm	65 lm/W	0 4 8 - 3 4 5 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	4000 K	1200 lm	67 lm/W	0 4 8 - 3 4 5 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



SASSO 100 round direct / indirect wall



OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
35.0 W	2700 K	↓1110/↑1110 lm	63 lm/W	0 4 8 - 3 4 6 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	3000 K	↓1150/↑1150 lm	66 lm/W	0 4 8 - 3 4 6 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 3500 K/ ↑3000 K	↓1170/↑1170 lm	67 lm/W	0 4 8 - 3 4 6 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O
	↓ 4000 K/ ↑4000K	↓1200/↑1200 lm	69 lm/W	0 4 8 - 3 4 6 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> O



Optical accessories (optional)



HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100

COLOUR	Ø-H (mm)	ORDER CODE
jet black	50.3	0 0 7 - 1 9 6 5 5 9 8

Order options

CONTROL	COLOUR	INNER COLOUR
non DIM	1 jet black RAL 9005	1 jet black RAL 9005
DALI-2	3 traffic white RAL 9016	7 matt silver
		4 traffic white RAL 9016
		7 gold dust RAL 260-M
		9

MAM Competence Center, Großhöflein

Österreich

Architekt

INNOCAD Architektur
ZT

Lighting Design

INNOCAD Architektur
ZT

Fotograf

Paul Ott



Verwendete Produkte




**SASSO 100 round
suspended**



**TASK round
suspended**



LITO 60 suspended



**SASSO 100 round
wall**



SONIC free standing

