

Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16
bis zu ↓ 3.810 lm / ↑ 3.700 lm
bis zu 179 lm/W
L90 / 100000 h
DALI-2, DALI-2 ESSENTIAL sensor
IP20

Types





Lichtverteilung





DIN EN 12464-1
UGR ≤ 16



up to 179 lm/W
(high efficiency)



ESSENTIAL
sensor available



sustainable
materials



Cradle to
Cradle
Certified®
(louver,
spotline)

ENVIVA

suspended

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; optionally with sensor

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; extrem schlanke Bauform (nur 45 x 15 mm); keine sichtbaren Schrauben; Oberfläche roh oder pulverbeschichtet; abgependelt mit Seilabhängung; stufenlos höhenverstellbar; inkl. Einspeiseleitung; linearer Lichteinsatz aus Kunststoff; bestückt mit LED Einzellichtpunkten; gute Entblendung durch zurückversetzte Lichtpunktebene; trotzdem erhöhte Effizienz durch spezielle Linsentechnik; eingesetzte Linsen mit wide flood Abstrahlcharakteristik; oder hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit symmetrischer Lichtverteilung; direkt / indirekte Abstrahlcharakteristik; effiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; Konverter im Baldachin enthalten; wahlweise mit Sensor



ENVIVA suspended

CRI ≥90 | UGR ≤10 | cd/m² ≤1500 | 1 ADDR. | X-PERT | presence | brightness



LOUVER | 1204 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
41.0 W	3000 K	80	↧3400/↥3080 lm	158 lm/W	067-021450 X
		90	↧2960/↥2650 lm	137 lm/W	067-021400 X
	4000 K	80	↧3620/↥3500 lm	174 lm/W	067-021460 X
		90	↧2960/↥2870 lm	142 lm/W	067-021410 X

sensor version +41mm; order canopy 850mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

LOUVER | 1504 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
41.0 W	3000 K	80	↧3460/↥3100 lm	160 lm/W	067-021550 X
		90	↧3010/↥2670 lm	139 lm/W	067-021500 X
	4000 K	80	↧3680/↥3520 lm	176 lm/W	067-021560 X
		90	↧3010/↥2880 lm	144 lm/W	067-021510 X

sensor version +41mm; order canopy 850mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

SPOTLINE | 1204 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
44.0 W	3000 K	80	↧3560/↥3250 lm	155 lm/W	067-121450 W
		90	↧3100/↥2800 lm	134 lm/W	067-121400 W
	4000 K	80	↧3790/↥3700 lm	170 lm/W	067-121460 W
		90	↧3100/↥3030 lm	139 lm/W	067-121410 W

sensor version +41mm; order canopy 900mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

SPOTLINE | 1504 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
43.0 W	3000 K	80	↧3580/↥3250 lm	159 lm/W	067-121550 W
		90	↧3110/↥2800 lm	137 lm/W	067-121500 W
	4000 K	80	↧3810/↥3700 lm	175 lm/W	067-121560 W
		90	↧3110/↥3030 lm	143 lm/W	067-121510 W

sensor version +41mm; order canopy 900mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

LENS | 1204 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
33.0 W	3000 K	80	↧2990/↥2380 lm	163 lm/W	067-221450 W
		90	↧2600/↥2050 lm	141 lm/W	067-221400 W
	4000 K	80	↧3180/↥2710 lm	178 lm/W	067-221460 W
		90	↧2600/↥2220 lm	146 lm/W	067-221410 W

sensor version +41mm; order canopy 850mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

Order options

CONTROL	
DALI-2	1
stand alone ESSENTIAL sensor	7
DALI-2 ESSENTIAL sensor	B

COLOURS	
aluminium raw / Cable white	0
aluminium raw / Cable black	1
traffic white / Cable white	7
jet black / Cable black	8

INSET	
chrome reflector	4
black reflector	8

INSET	
chrome	4
traffic white RAL 9016	7
jet black RAL 9005	8

LENS | 1504 MM | DIRECT / INDIRECT

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
31.0 W	3000 K	80	↧2660/↥2380 lm	163 lm/W	067-221555 ◪ W
		90	↧2320/↥2050 lm	141 lm/W	067-221505 ◪ W
	4000 K	80	↧2830/↥2710 lm	179 lm/W	067-221566 ◪ W
		90	↧2320/↥2220 lm	146 lm/W	067-221511 ◪ W

sensor version +41mm; order canopy 850mA separately; DALI-2 application controller for DALI-2 essential sensor variants needed

Electrical accessories (required)



CANOPY square incl. converter DALI-2, 44 W, 176-264 V AC, PC2

TYPE	EFFICIENCY	TYPE	L·W·H (mm)	ORDER CODE
	η 89 %		112·112·35	005-261103 ◪
stand alone sensor	η 89 %	stand alone sensor	112·112·35	005-261107 ◪
	η 89 %		112·112·35	005-261113 ◪
stand alone sensor	η 89 %	stand alone sensor	112·112·35	005-261177
stand alone sensor	η 89 %	stand alone sensor	112·112·35	005-261178

Order options

CONTROL ◆		COLOURS ◪		COLOUR ◪	
DALI-2	1	aluminium raw / Cable white	0	traffic white RAL 9016	7
stand alone ESSENTIAL sensor	7	aluminium raw / Cable black	1	jet black RAL 9005	8
DALI-2 ESSENTIAL sensor	B	traffic white / Cable white	7		
		jet black / Cable black	8		