




Quickinfo

2700 K, 3000 K, 4000 K
 CRI \geq 90 / 3 SDCM (initial MacAdam)
 UGR \leq 10, UGR \leq 13, UGR \leq 16, UGR \leq 19
 bis zu 80 lm/W
 L85 / 50000 h
 DALI-2, nicht dimmbar
 front IP44, back IP20

Types



Farbe



Montage Set



Lichtverteilung



SASSO 40 round downlight

recessed 2 lamps

EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering


DE Runder Einbaustrahler; werkzeuglose Montage im Montageset durch Kugelschnappsystem; Oberfläche lackiert; mit umlaufendem Rand; zweiflämmig; präzise Abstrahlcharakteristik durch hochwertige Linsenoptik; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe



glare control
(UGR \leq 16)



SASSO 40 round downlight



SPOT 15°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x5.1 W,	2700 K	2x368 lm	72 lm/W	0 4 8 - 2 8 0 0 4 1 <input checked="" type="checkbox"/> S
12 Vf,	3000 K	2x396 lm	78 lm/W	0 4 8 - 2 8 0 0 5 1 <input checked="" type="checkbox"/> S
450 mA	4000 K	2x396 lm	78 lm/W	0 4 8 - 2 8 0 0 6 1 <input checked="" type="checkbox"/> S




MEDIUM 25°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x5.1 W,	2700 K	2x377 lm	74 lm/W	0 4 8 - 2 8 0 0 4 1 <input checked="" type="checkbox"/> M
12 Vf,	3000 K	2x405 lm	79 lm/W	0 4 8 - 2 8 0 0 5 1 <input checked="" type="checkbox"/> M
450 mA	4000 K	2x405 lm	79 lm/W	0 4 8 - 2 8 0 0 6 1 <input checked="" type="checkbox"/> M

FLOOD 46°, CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x5.1 W,	2700 K	2x381 lm	75 lm/W	0 4 8 - 2 8 0 0 4 1 <input checked="" type="checkbox"/> F
12 Vf,	3000 K	2x410 lm	80 lm/W	0 4 8 - 2 8 0 0 5 1 <input checked="" type="checkbox"/> F
450 mA	4000 K	2x410 lm	80 lm/W	0 4 8 - 2 8 0 0 6 1 <input checked="" type="checkbox"/> F

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L-W-H (mm)

122-60-13

ORDER CODE

0 4 8 - 2 8 9 8 3 1


Electrical accessories (required)

POWER SUPPLY 450 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
23 W non DIM	η 88 %	138-30-21	0 0 2 - 9 0 7 5 2
15 W DALI-2	η 87 %	147-33-23	0 0 2 - 9 0 7 5 3

Electrical accessories (optional)

DIN RAIL POWER SUPPLY BASIC 48 V



TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

Order options

COLOUR		COLOUR	
jet black RAL 9005	1 <input checked="" type="checkbox"/>	traffic white RAL 9016	7 <input checked="" type="checkbox"/>
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7		
gold dust RAL 260-M	9		

DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses 200 -1050 mA settable const. current 2×42W 48V DC U OUT 10–40V	36-88-59	0 0 5 - 6 1 2 1 0 3 0

POWER SUPPLY PRE-WIRED with junction box DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
450 mA	η 87 %	0 0 2 - 9 0 7 5 0 A
200 mA	η 87 %	0 0 2 - 9 0 7 4 9 A

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 5 0
200 mA	η 87 %		0 0 2 - 9 0 7 4 9

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7		
gold dust RAL 260-M	9		