



SASSO 40 round wallwasher

recessed 2 lamps


EN Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler; werkzeuglose Montage im Montageset durch Kugelschnappsystem; Oberfläche lackiert; mit umlaufendem Rand; zweiflammig; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofaccettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI \geq 90 / 3 SDCM (initial MacAd
bis zu 110 lm/W
L85 / 50000 h
DALI-2, nicht dimmbar
front IP20

Types



Farbe



Montage Set



Lichtverteilung



wallwasher/
wallwasher floor
inset



SASSO 40 round wallwasher



WALLWASHER CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|----------|--------------|-----------|----------|---|
| 2x6.9 W, | 2700 K | 2x761 lm | 110 lm/W | 0 4 8 - 2 8 4 0 9 1 <input checked="" type="checkbox"/> A |
| 36 Vf, | 3000 K | 2x731 lm | 106 lm/W | 0 4 8 - 2 8 4 0 0 1 <input checked="" type="checkbox"/> A |
| 200 mA | 3500 K | 2x761 lm | 110 lm/W | 0 4 8 - 2 8 4 0 2 1 <input checked="" type="checkbox"/> A |
| | 4000 K | 2x701 lm | 101 lm/W | 0 4 8 - 2 8 4 0 1 1 <input checked="" type="checkbox"/> A |




The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

Mounting accessories (required)

MOUNTING SET with trim 2 lamps 2-25 mm, for intermediate ceilings

| COLOUR | L-W-H (mm) | ORDER CODE |
|---------------|------------|-----------------------|
| traffic white | 122-60-13 | 0 4 8 - 2 8 9 8 3 1 7 |
| jet black | 122-60-13 | 0 4 8 - 2 8 9 8 3 1 8 |



Electrical accessories (required)

POWER SUPPLY PC2, 198-264 V AC, 200 mA

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|----------------|------------|------------|-------------------|
| 45 W DALI-2 | η 91 % | 165-29-21 | 0 0 2 - 9 0 7 4 0 |
| 10 W non DIM | η 80 % | 65-39-20 | 0 0 2 - 9 0 7 4 4 |

Electrical accessories (optional)

DIN RAIL LED DRIVER

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|-----------------------|
| DALI-2 DT6 1-2 addresses | 36-88-59 | 0 0 5 - 6 1 2 1 0 3 0 |

200 - 1050 mA settable const. current | 2x42W | 48V DC | U OUT 10-40V

DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|-------------|---------------|------------|------------|-----------------------|
| 160 W PC2 | 220-240 V AC | η 94 % | 72-90-63 | 0 0 5 - 6 5 2 0 2 1 0 |

Lifetime @ 120W, 45° ambient temp., cascable max. 3 devices

POWER SUPPLY PRE-WIRED with junction box PC2, 15 W, 198-264 V AC, DALI-2

| TYPE | EFFICIENCY | ORDER CODE |
|--------|------------|---------------------|
| 450 mA | η 87 % | 0 0 2 - 9 0 7 5 0 A |
| 200 mA | η 87 % | 0 0 2 - 9 0 7 4 9 A |

POWER SUPPLY with loop through function PC2, 15 W, 198-264 V AC, DALI-2

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|--------|------------|------------|-------------------|
| 450 mA | η 87 % | 185-30-21 | 0 0 2 - 9 0 7 5 0 |
| 200 mA | η 87 % | | 0 0 2 - 9 0 7 4 9 |

Order options

| COLOUR | |
|------------------------|---------------------------------------|
| jet black RAL 9005 | 1 <input checked="" type="checkbox"/> |
| matt silver | 4 |
| traffic white RAL 9016 | 7 |
| gold dust RAL 260-M | 9 |